



PowerWalker VI 750 R1U Line- Interactive 0.75 kVA 450 W 4 AC outlet(s)

Model: VI 750 R1U

Manufacturer: POWER WALKER

EAN: 4260074980394

Product Code: 1021741

R5,056

Power protection features: Overload | Typical backup time at half load: 8.7 min | Typical backup time at full load: 0.4 min | Input frequency: 45/55 Hz | Emergency Power Off (EPO) connector: Yes | Output voltage regulation: 10% | AC outlets quantity: 4 AC outlet(s) | Package width: 537 mm | Cables included: Input power cable, USB cable | UPS topology: Line-Interactive | Width: 433 mm | Number of batteries supported: 2 | Operating relative humidity (H-H): 0 - 95% | Display type: LCD | Battery capacity: 9 Ah | Height: 44 mm | Output operation voltage (min): 230 V | Package height: 150 mm | Depth: 216 mm | AC outlet types: C13 coupler | Output frequency regulation: 0.5 Hz | RS-232 ports: 1 | Rack capacity: 1U | USB port: Yes | Output power capacity: 0.75 kVA | Weight: 8.6 kg | Output operation voltage (max): 230 V | Operating temperature (T-T): 0 - 40 °C | Battery voltage: 6 V | Waveform: Sine | Manual: Yes | Form factor: Rackmount | Input operation voltage (min): 165 V | Output power: 450 W | Product colour: Black | Input operation voltage (max): 290 V | Output power factor: 0.6

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950