



Axagon PCEM2-D PCIe x4 - M.2 NVMe M-key + SATA B-key slot adapter w. SP & LP

Model: PCEM2-D

Manufacturer: AXAGON

EAN: 8595247903846

Product Code: 1054996

R1,096

The internal AXAGON PCEM2-D adapter allows to connect as many as two M.2 SSD to a desktop. So, it is an ideal choice for upgrading a desktop that has no M.2 slot.

The adapter supports the use of both one-sided and double-sided SATA and NVMe (PCI-Express) M.2 SSDs. The reduction does not limit SSD capacity, and any M.2 cards with a length up to 110 mm can be used. The simultaneous operation of both disks is commonplace.

Thanks to PCI-Express 3.0 4-lane interface compatible with x4, x8 and x16 slots, a speed as high as 8GBps can be achieved. When compared to standard SATA SSDs, bit rates of NVMe SSDs are many times higher.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The high quality card design, including copper-plated vents, assists in a better dissipation of heat generated during the M.2 SSDs operation.

Double blue LEDs indicate either power on or data transfer in the M.2 slot. The package also contains a low profile blanking plug for mounting the adapter into low profile cases.

Input:

- PCI-Express 3.0 interface compatible with PCI-Express 1.0a / 1.1 / 2.0 / 2.1.
- Number of 4-Lane lines, compatible with x4 / x8 / x16 PCIe slots.
- Bandwidth of 4-Lane PCI-Express 3.0 bus of up to 8 GB/s (two-way).
- SATA connector to connect the motherboard when a SATA M.2 SSD is used. To achieve the best possible bit rates, the use of a SATA 6G controller is recommended.

Output:

- NGFF 75-pin M-key slot to install the NVMe (PCI-Express) M.2 SSDs.
- NGFF 75-pin B-key slot to install the SATA (AHCI) M.2 SSDs

Other features:

- Full Plug and Play support.
- Support of M.2 disks of any size - 2230, 2242, 2260, 2280, 22110 mm.
- Support of M.2 disks of any capacity.
- Simultaneous operation of both disks.
- Support of both one-sided and double-sided M.2 disks.
- A better dissipation of heat from M.2 SSDs thanks to copper-plated vents.
- Support of booting from SSD cards.
- No drivers need to be installed.
- Note: CAUTION! The adapter allows to insert B+M-key disks in both M.2 slots. It is important to check the disk parameters, i.e. to make sure whether the disk is designed for SATA or NVMe (PCI Express) interface, and to connect it to the right slot. SATA drives are plugged into the B-key slot, NVMe drives are plugged into the M-key slot.

Power supply:

- The adapter is directly supplied from PCI-Express bus; no external power supply is needed.
- The system of dual power supply ensures a sufficient power for connected M.2 SSDs.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- In addition, the system of redundant power supply reduces the adapter thermal load.

Supported operating systems:

- MS Windows 7 / 8 / 8.1 / 10, Windows Server 2008 R2 / 2012 / 2016 (all 32-bit as well as 64-bit versions of OS Windows are supported), Linux with kernel 2.6.31 and higher.
- Note: When operating under Windows 7, contact the manufacturer of the M.2 SSD to find whether this OS is supported, especially when NVMe disks are used.

Package contains:

- PCI-Express adapter with a standard blanking plug,
- low profile blanking plug,
- mounting material and a screwdriver,
- printed installation manual EN/CZ/DE/ESP/FR/HU/IT/PL/RO/RU/SK/BG,
- packed in a cardboard box with clearly indicated parameters.