



Axagon RUCM-AFAC cable adapter USB-C (M) -> USB-A (F), 20cm, USB 3.2 Gen 1, 3A, ALU

Model: RUCM-AFAC

Manufacturer: AXAGON

EAN: 8595247905994

Product Code: 1059574

R855

Cable adapter USB-C -> USB-A AXAGON RUCM-AFAC connects existing devices with a USB-A connector to any new device with a modern USB-C interface.

Adapter is designed for quick connection of a USB hub or external drive to notebooks equipped with only USB-C connectors. It is also great for connecting a flash drive to a mobile phone with a USB-C connector. It supports data transfer speeds of up to 5 Gb/s and power supplies of up to 3A.

The reduction is equipped with metal terminals, connectors with a nickel-plated surface and gold-plated contacts. Cable conductors are made of Tin-plated oxygen free copper. High-quality cable

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

insulation, made of flexible TPE, guarantees maximum durability and also maintains sufficient flexibility. Triple shielding protects transmitted signals from adverse interference.

Connectors:

- vstup USB-C (M) male.
- výstup USB-A (F) female.

Other Features:

- DATA SYNC & FAST CHARGING - simultaneous data transfer and mobile device battery charging.
- SuperSpeed USB - USB 3.2 Gen 1 (formerly USB 3.1 Gen 1 / USB 3.0).
- Compatible with USB 3.2 Gen 2, backward compatible with USB 2.0.
- Supports 5.000 / 480 / 12 / 1.5 Mb/s (SuperSpeed / High / Full / Low speed) transmission rates.
- Support for high-speed charging by current up to 3A.
- Cable includes power wires 22AWG, data wires 30AWG.

Tin-plated oxygen free copper conductors to reduce oxidation, increase conductivity, and clear signal without distortion.

- Double shielding via galvanized foil and oxygen free copper braiding minimizes interference and prevents signal loss.
- Nickel-plated connectors and gold-plated contacts prevent oxidation and provide a reliable connection.
- Pulldown resistor 5 kΩ.
- Suitable for notebooks, mobile phones and smartphones, powerbanks, tablets and other mobile devices with USB-C connector.

Other data:

- cable length 0.2 m,
- 4.2 mm outer diameter.

Package contains:

- USB-C M -> USB-A F cable adapter,
- packed in a printed and sealed foil package with hanging hole.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950