



InLine HDMI AOC cable, Ultra High Speed HDMI, 8K4K, detachable plug, 80m



Model: 179800

Manufacturer: INLINE

EAN: 4043718333776

Product Code: 1081549

R3,812

Flexible installation thanks to narrow installation paths: Removable HDMI A and HDMI D connectors allow easy routing through cable ducts – ideal for AV installations.

Loss-free signal quality: Active optical HDMI 2.1 technology enables high-resolution video and audio signals in the highest quality.

Versatile combination options: 4-in-1 solution – can be used as HDMI-A/D in both directions, ideal for different connection environments.

Industrial-grade design: Hybrid construction made of fibre optic and copper with aramid protection, gold-plated contacts and robust metal connectors.

Future-proof equipment: Supports 8K@60Hz, 4K@120Hz, HDR, eARC, CEC, HDCP and much more – for professional AV and IT applications.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The InLine® HDMI AOC cable with detachable HDMI plugs is the well-designed solution for professional AV installations with the highest demands on resolution, flexibility and signal quality. Thanks to active optical transmission via fibre optics, it ensures stable, loss-free signal transmission – ideal for digital signage systems, conference rooms or home cinema systems.

The hybrid design of fibre optic and copper, combined with aramid protective braiding and gold-plated contacts, ensures maximum robustness, durability and minimal signal interference. The HDMI A and HDMI D connectors can be removed without tools, making installation in tight spaces particularly easy – perfect for cable ducts, cabinets and flush-mounted solutions.

The cable supports HDMI 2.1 features such as 8K at 60 Hz or 4K at 120 Hz, Dynamic HDR, eARC, HDCP 2.3 and much more, making it ideally equipped for future requirements in presentation technology, entertainment, streaming or broadcasting. The 4-in-1 connection options offer maximum flexibility in practice.

HDMI version: HDMI 2.1 (Ultra High Speed HDMI)

Transmission rate: up to 48 Gb/s

Construction: 4 glass fibres + 7 copper conductors, hybrid

Diameter: 4.8 mm

Temperature range: operation 0 °C to +50 °C, storage -20 °C to +70 °C

Connector: HDMI-A (standard), HDMI-D (micro), detachable

Supported functions: HDR, eARC, HDCP, CEC, DDC, EDID, 3D, Dynamic HDR

Directional (source → display)

Contact material: gold-plated

Connector housing: metal, aramid-protected

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950