



InLine 17991A cable gender changer HDMI A Grey



Model: 17991A

Manufacturer: INLINE

EAN: 4043718338184

Product Code: 1081550

R855

Stable A/V signal transmission: Direct 1:1 pin mapping ensures reliable transmission of audio and video signals without conversion or loss of quality.

Optimized for high-resolution applications: Supports UHD-8K and has been successfully tested in practice with 3840x2160 at 120 Hz and 4:4:4 8bit.

Durable contact technology: Gold-plated contacts provide a permanently secure connection and reduce contact resistance in professional use.

Robust aluminum housing: The compact metal housing ensures protection against mechanical influences and supports reliable use even in demanding installations.

Flexible signal routing: Ideal for connecting or extending two HDMI cables in media technology, digital signage, or industrial visualization systems.

The HDMI adapter connects two HDMI cables and serves as a flexible extension of existing signal paths. The 1:1 pin assignment enables direct, unadulterated transmission of digital audio and video signals. This makes the adapter suitable for installations that require stable, high-quality

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

transmission paths.

The adapter supports resolutions up to UHD 8K and has been successfully tested in practical application tests with 3840x2160 at 120 Hz and 4:4:4 8bit. The gold-plated contacts ensure permanently low contact resistance and a reliable connection throughout the entire service life. The compact aluminum housing protects the internal contacts and ensures high robustness. Thanks to its passive design, the adapter can be flexibly integrated into signal paths. The adapter is suitable for media technology, digital signage, presentation and visualization systems, and other professional A/V applications where a secure and low-loss HDMI connection is required. The total link length is recommended to be up to 1.5 meters and can be a maximum of 2 meters. Thanks to its compact design, the adapter can be easily integrated into rack systems, wall installations, or mobile setups.

Audio: Yes

Housing material: Aluminum

Side A: HDMI A female connector

Side B: HDMI A female connector

Signal type: Audio/video

Contact resistance: 3 ohms

Insulation resistance: DC 300V 10M ohms

Operating temperature: -10 °C to +60 °C

Storage temperature: -20 °C to +80 °C

Dimensions: 29.2 mm x 19.3 mm x 9.5 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950