



InLine 17991B cable gender changer HDMI A Micro HDMI D Black, Grey

Model: 17991B

Manufacturer: INLINE

EAN: 4043718338191

Product Code: 1081551

R855

Reliable signal transmission:The 1:1 pin assignment enables direct transmission of audio and video signals without conversion.

Suitable for high-resolution applications:Supports UHD 8K and has been successfully tested in practice with 3840x2160 at 120 Hz and 4:4:4 8 bits.

Durable contact technology:Gold-plated contacts ensure stable transitions and reduce electrical resistance.

Robust construction:The aluminum housing protects the internal components and is suitable for demanding installations.

Flexible integration:Ideal for connecting or extending HDMI connections between micro HDMI sources and standard HDMI infrastructures.

The HDMI adapter reliably connects devices with micro HDMI outputs to existing HDMI infrastructure.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The HDMI A socket on one side and the micro HDMI D plug on the other enable direct signal transmission without the need for additional active components. The 1:1 pin assignment ensures unadulterated transmission of digital audio and video signals.

The adapter supports resolutions up to UHD 8K and has been successfully tested with 3840x2160 at 120 Hz and 4:4:4 8 bits. This makes it suitable for installations that require high image quality and stable signal paths. The gold-plated contacts reduce contact resistance and contribute to a permanently reliable connection.

The robust aluminum housing protects the contact surfaces and ensures high mechanical stability. The adapter can be flexibly integrated into both stationary and mobile AV setups. The recommended total length of the signal path is up to 1.5 meters and can reach a maximum of 2 meters.

With its compact design, the adapter offers a reliable solution for various professional applications in which micro HDMI signals need to be integrated into existing HDMI environments.

Audio: Yes

Housing material: Aluminum

Side A: HDMI A socket

Side B: Micro HDMI D plug

Signal type: Audio/video

Type: Gold-plated contacts

Contact resistance: 3 ohms

Insulation resistance: DC 300V 10M ohms

Operating temperature: -10 °C to +60 °C

Storage temperature: -20 °C to +80 °C

Recommended total length: up to 1.5 m, maximum 2 m

Dimensions: 19.3 mm x 12 mm x 10 mm

Outer jacket: PVC black

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950