



InLine 17991D cable gender changer HDMI A Black, Grey



Model: 17991D

Manufacturer: INLINE

EAN: 4043718338214

Product Code: 1081553

R855

Space-saving installation:The 90-degree angle allows connection in tight spaces and reduces stress on the HDMI port.

Uncompromised signal transmission:The 1:1 pin assignment supports stable transmission of digital audio and video signals.

Suitable for high-resolution applications:Supports UHD 8K and has been tested in practice with 3840x2160 at 120 Hz and 4:4:4 8 bits.

Reliable contact technology:Gold-plated contacts reduce contact resistance and ensure permanently stable signal paths.

Robust aluminum housing:The metal construction protects the internal contact surfaces and is suitable for demanding installation environments.

The HDMI adapter enables the connection or redirection of an HDMI cable in space-critical installations. The 90-degree angle facilitates use in areas where there is little distance between the device and the wall. The HDMI A plug and socket side allows direct integration into existing HDMI

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

routes without additional active components.

The 1:1 pin assignment ensures unadulterated transmission of digital audio and video signals. The adapter supports resolutions up to UHD 8K and has been successfully tested in practice with 3840x2160 at 120 Hz and 4:4:4 8 bits. Gold-plated contacts minimize contact resistance and contribute to stable signal transmission.

The robust aluminum housing protects the contact surfaces and allows use in stationary and mobile installations. The recommended total length of the signal connection is up to 1.5 meters and can reach a maximum of 2 meters.

The compact design makes the adapter suitable for installation environments where HDMI signals need to be safely and efficiently redirected or extended.

Item width: 2.9 cm

Item height: 1.0 cm

Item length: 4.2 cm

Audio: Yes

Housing material: Aluminum

Outer jacket: Black PVC

Side A: HDMI A plug

Side B: HDMI A socket

Angle direction: 90 degrees right

Signal type: Audio/video

Type: Gold-plated contacts

Contact resistance: 3 ohms

Insulation resistance: DC 300V 10M ohms

Operating temperature: -10 °C to +60 °C

Storage temperature: -20 °C to +80 °C

Recommended total length: up to 1.5 m, maximum 2 m

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950