



InLine 32335R network transceiver module Fiber optic 2500 Mbit/s SFP 850 nm



Model: 32335R

Manufacturer: INLINE

EAN: 4043718338078

Product Code: 1081628

R1,438

High-quality SFP transceiver module for a fast 2.5 gigabit data connection
Optical LC duplex interface for multimode fiber optics with 850nm wavelength
Digital diagnostic monitoring (DDM) for real-time performance control
Hot-pluggable for easy installation and flexible replacement
Operating temperature from 0 °C to 70 °C for reliable performance

The InLine® SFP module is a reliable solution for setting up and expanding network structures with a transmission rate of 2.5 Gb/s over multimode fiber optics. With a range of up to 300 meters, it is ideal for use in corporate networks, data centers and backbone connections.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

This module has an optical LC duplex interface and is fully compatible with standard SFP connectors, allowing easy integration into existing network infrastructures. Digital Diagnostic Monitoring (DDM) allows precise control of performance parameters in real time to ensure network security and efficiency.

Thanks to the hot-pluggable function, the module can be easily replaced or installed without affecting ongoing operations. The robust design ensures reliable performance at an operating temperature of 0 °C to 70 °C.

Technical specifications:

Wavelength: 850nm

Optical interface: LC Duplex

Transmission distance: 300 m (multimode fiber optics)

Digital diagnostics and monitoring (DDM)

Operating voltage: +3.3 V

Hot-pluggable design

Operating temperature: 0 °C to 70 °C

Storage temperature: -40 °C to 85 °C

Note on coding:

Our SFP modules are factory-coded – whether for Cisco, Intel or other systems, which may limit your choice.

For maximum compatibility, we now programme individually according to customer requirements.

Please contact your sales representative.