



InLine 32335S network transceiver module Fiber optic 2500 Mbit/s SFP 1310 nm



Model: 32335S

Manufacturer: INLINE

EAN: 4043718338085

Product Code: 1081629

R1,531

High-quality SFP transceiver module for a fast 2.5 gigabit data connection
Optical LC duplex interface for single-mode fiber optics with 1310nm wavelength
Digital diagnostic monitoring (DDM) for real-time performance control
Hot-pluggable for easy installation and flexible replacement
Operating temperature from 0 °C to 70 °C for reliable performance

The InLine® SFP module is a reliable solution for setting up and expanding network structures with a transmission rate of 2.5 Gb/s over single-mode fiber optics. With a range of up to 15 kilometers, it is ideal for use in corporate networks, data centers and backbone connections.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

This module has an optical LC duplex interface and is fully compatible with standard SFP connectors, allowing easy integration into existing network infrastructures. Digital Diagnostic Monitoring (DDM) allows precise control of performance parameters in real time to ensure network security and efficiency.

Thanks to the hot-pluggable function, the module can be easily replaced or installed without affecting ongoing operations. The robust design ensures reliable performance at an operating temperature of 0 °C to 70 °C.

Technical specifications:

Wavelength: 1310nm

Optical interface: LC Duplex

Transmission distance: 15 km (single-mode fiber optic)

Digital diagnostics and monitoring (DDM)

Operating voltage: +3.3 V

Hot-pluggable design

Operating temperature: 0 °C to 70 °C

Storage temperature: -40 °C to 85 °C

Note on coding:

Our SFP modules are factory-coded – whether for Cisco, Intel or other systems, which may limit your choice.

For maximum compatibility, we now programme individually according to customer requirements.

Please contact your sales representative.