InLine 33271A interface hub USB 3.2 Gen 1 (3.1 Gen 1) Type-C 5000 Mbit/s Grey

Model: 33271A

Manufacturer: INLINE

EAN: 4043718349289

Product Code: 1081636

R1,096

Efficient expansion via USB-C: The hub adds three USB-A ports, HDMI video output, and USB-C Power Delivery to USB-C-enabled devices.

High-resolution HDMI output: Supports resolutions up to 3840 x 2160 at 60 Hz for connecting external displays.

Power supply with up to 100 W: The USB-C Power Delivery input forwards the power to the connected device.

Durable aluminum housing: Ensures mechanical stability and long-lasting use in everyday applications.

Cross-system compatibility: Works with Windows, macOS, and Linux without additional drivers.

The InLine® multifunction hub offers a reliable way to use multiple functions simultaneously via a

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

single USB-C connection. The device provides three USB-A ports that support USB 3.2 Gen.1. These enable data transfers at up to 5 Gb/s and are suitable for connecting common peripheral devices. The integrated HDMI port allows image signals of up to 3840 x 2160 at 60 Hz to be transmitted to external monitors or projectors. This enables use in multimedia work environments and for presentation purposes. An additional USB-C Power Delivery input is used for power supply. When connected to a suitable power supply, the connected device can be supplied with up to 100 W. The robust aluminum housing reliably protects the internal electronics. The hub is connected via a permanently integrated USB-C cable. Support for Windows, macOS, and Linux operating systems ensures high flexibility when integrating into existing systems.

3x USB-A: USB 3.2 Gen.1, up to 5 Gb/s
1x HDMI: up to 3840 x 2160 @ 60 Hz
1x USB-C Power Delivery: PD up to 100 W
Housing material: Aluminum
Supported operating systems: Windows, macOS, Linux
Operating temperature: 0 °C to +40 °C
Storage temperature: -20 °C to +60 °C
Permissible humidity: 20-80%, non-condensing

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950