

InLine 57885E KVM switch Rack mounting Black

Model: 57885E

Manufacturer: INLINE

EAN: 4043718344284

Product Code: 1081713

R3,441

Two devices – one workspace: Switch easily between an HDMI and a USB-C device with just one display, keyboard and mouse.
Excellent image quality: Supports 4K@60Hz with 4:4:4 colour sampling and Dolby Vision – crystal-clear images for professional demands.
Flexible control: Switch via hotkey, IR remote control, front button or RS-232 – ideal for individual setups or automation.
Universal compatibility: Works with Windows, macOS and Linux – no driver installation required.
Additional functionality:USB-C devices can be charged simultaneously and USB peripherals can be used at up to 5 Gb/s.

The InLine® KVM switch with 2-way switching via HDMI and USB-C offers a convenient way to operate two computers with just one monitor, one keyboard and one mouse. Video output is in brilliant 4K resolution at 60 Hz with full support for modern HDR formats such as Dolby Vision or HDR10+.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Thanks to four USB 3.2 Gen.1 ports, a mouse, keyboard and other peripherals such as external drives or webcams can be used centrally. Particularly practical: the integrated charging function with USB-C Power Delivery (PD 3.0) allows a connected end device to be powered simultaneously. Switching is flexible via front button, IR remote control, hotkeys or RS-232 interface – also ideal for professional IT setups or automated applications. The switch is completely driver-free and can be used immediately with Windows, macOS or Linux.
The robust metal housing, comprehensive signal support and ESD protection round off the professional appearance.
The InLine® KVM switch is therefore the ideal solution for home offices, training courses, system integration and demanding workstation environments.

HDMI input: 1 × HDMI (type A, 19-pin)
USB-C input: 1 × USB-C (AV signal), 1 × USB-C (charging function, PD 3.0)
HDMI output: 1 × HDMI (type A, 19-pin)
USB ports: 4 × USB 3.2 Gen.1 (USB-A), 1 × USB host (USB-B)
RS-232: 3-pin terminal connection
IR EXT: 3.5 mm stereo jack (38 kHz)
Audio output: 3.5 mm stereo jack (PCM 2.0CH)
Resolution: up to 4K@60Hz, 2K@144Hz
Colour depth: 8 / 10 / 12 bits
Colour spaces: RGB 4:4:4, YCbCr 4:4:4, 4:2:2, 4:2:0
HDR support: HDR, HDR10, HDR10+, Dolby Vision, HLG
HDMI version: HDMI 2.0
DP compatibility: DP 1.4 (for USB-C input)
HDCP compatibility: HDCP 2.3
Supported audio formats HDMI IN/OUT: LPCM, Dolby Digital/Plus/EX, Dolby TrueHD, Dolby Atmos, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DTS:X, DSD
Latency: no video or audio delay
CEC support: yes
ESD protection: ±8 kV air / ±4 kV contact
Housing: metal, black
Dimensions: 175 × 100 × 30 mm
Weight: 505 g
Operating temperature: 0–40 °C

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Storage temperature: –20–60 °C

Humidity: 20–90% (non-condensing)

Recommended cable lengths

HDMI: up to 5 m (4K@60Hz), up to 10 m (1080p)

USB-C: up to 1.5 m

Note: Use of ‘Premium High Speed HDMI’ or ‘USB-C’ cables recommended

External power supply (power adapter)

Type: External plug-in power adapter with lock

Input voltage: 100–240 V AC, 50/60 Hz

Output voltage: 12.0 V DC

Output current: max. 1.0 A

Output power: 12.0 W

Average operating efficiency: 85.23%

Efficiency at low load (10%): 78.53%

Power consumption at zero load: 0.09 W

Scope of delivery

1 × InLine® KVM switch, 2-port, HDMI, USB-C, 4K60Hz

1 × IR remote control

1 × IR receiver cable (1.5 m, 38 kHz)

1 × HDMI cable (1.5 m)

1 × USB cable (USB 3.2 Gen.1, USB-A to USB-B, 1.8 m)

1 × USB-C cable (USB 3.2 Gen.2, male on both sides, 1 m)

1 × 12 V/1 A power supply with lock

1 × 3-pin terminal connection plug

2 × mounting brackets

4 × screws (KM3×4)

1 × user manual in German/English

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950