



InLine 65010K video switch HDMI



Model: 65010K

Manufacturer: INLINE

EAN: 4043718336296

Product Code: 1081749

R2,271

Distributes one HDMI signal to up to four output devices - ideal for professional AV installations
Supports 4K2K@60Hz, 3D and Deep Color 12-bit for highest picture quality
Compatible with HDCP 1.4 and 2.2 - reliable in use with the latest end devices
High-quality processing and stable signal distribution - ideal for digital signage and presentation systems
Compact design and external power supply - easy to integrate into existing systems

The InLine® HDMI Splitter 65010K is the reliable solution for professional AV environments in which an HDMI signal needs to be distributed to multiple output devices. It enables simultaneous signal transmission from one HDMI source to up to four displays - without any loss of quality. With support for 4K2K@60Hz, 12-bit Deep Color and 3D, the device ensures brilliant picture quality in the highest resolution. Thanks to integrated HDCP decryption and encryption (compatible with HDCP Rev. 1.4/2.2), the splitter can be easily integrated into modern system landscapes. Audio formats such as Dolby TrueHD, DTS-HD Master Audio and LPCM 7.1 are transmitted loss-free - perfect for high-quality media presentations or installations in the digital signage sector. The compact design, combined with

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

a sturdy metal housing and a 5V power supply unit, makes the device ideal for use in AV racks, training rooms, conference systems or exhibitions. System houses and specialist retailers benefit from a reliable and easy-to-integrate solution that is compatible with common HDMI standards.

HDMI specification 2.0

Frequency range: 25 MHz - 600 MHz

Output current: max. 2.0 A / output power: 10 W

Input alternating current frequency: ~50/60Hz, 0.4 A

Average efficiency during operation: 79.96%

Power consumption at no load: 0.08 W