




InLine PCI Multi I/O Controller Card 2 DB9 Serial Ports



Model: 66636A

Manufacturer: INLINE

EAN: 4043718333233

Product Code: 1081750

R1,062

Reliable expansion for serial communication: Easily add two RS232 interfaces to your desktop system for industrial applications, legacy hardware and special projects.

Compatible with industry standards: Supports UART protocols (16C450/550/552) and ensures maximum flexibility when integrating into existing systems.

High transfer speed: The integrated CH351Q chipset enables stable data rates of up to 2 Mbps when both ports are used simultaneously.

Universal operating system support: Compatible with Microsoft Windows 98SE and above, as well as modern Linux kernels from 2.4.x for versatile use.

Easy installation in PCI systems: Thanks to the PCI V2.2 standard, you can install the card quickly and easily in almost any desktop system.

InLine® interface card, 2x 9-pin serial, PCI - Reliable expansion for your communication needs

The InLine® PCI interface card offers a simple and reliable way to expand your desktop systems with

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

two additional RS232 serial interfaces. Based on the proven CH351Q chipset, the card supports high transfer rates of up to 2 Mbps and ensures stable data communication – ideal for industrial control systems, older printing systems, serial networks and specialised hardware projects.

Chipset: WCH CH351Q

Bus interface: PCI V2.2

UART compatibility: 16C450, 16C550, 16C552

FIFO: 16 bytes for sending and receiving per connection

Maximum transfer rate: up to 2 Mbps

Supported modes: SPP, PS/2, EPP, ECP (IEEE1284 compatible)

Supported serial formats: 5-6-7-8 bits

Stop bits: 1 or 2

Flow control: CTS/RTS hardware handshake

Operating systems: Microsoft Windows 98SE or newer, Server 2003 or newer, Linux Kernel 2.4.x or newer

Operating temperature: 0° C – 55° C

Storage temperature: -40° C – 70° C

Humidity: 10% - 90% non-condensing