



InLine 69927Q cable accessory Cable coupler



Model: 69927Q

Manufacturer: INLINE

EAN: 4043718346844

Product Code: 1081766

R924

Compact USB-A coupling: Only 74 mm long – perfect for installations with limited space.

IP68-protected: Robust connection for demanding outdoor and industrial applications.

Data and power: 5 Gb/s transfer rate, 2 A current at 5 V – ideal for data transfer and charging.

Shielded housing: High EMC protection for interference-free connection in critical environments.

Tool-free installation: With screw mechanism and seal – safe, fast, reliable.

The InLine® USB-A cable connector in a short design with IP68 protection is the ideal solution for USB-A connections under extreme conditions. Its compact length of only 74 mm makes it ideal for confined installation locations, e.g., in outdoor enclosures, machines, or industrial systems.

With a USB-A socket on both sides, the shielded connector is designed for data transfers up to 5 Gb/s and charging with up to 2 A at 5 V. It thus meets all the requirements of a modern USB connection – both for industrial applications and for professional outdoor installations.

Thanks to the integrated screw mechanism, the coupling can be mounted quickly and without tools. The combination of a green sealing ring and rubber seal ensures reliable IP68 sealing – against dust, moisture, and mechanical stress.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The ideal solution for USB connections in demanding environments where reliability, protection, and compactness are required.

Material: Nylon (PA66)

Thread size: M20

Module: USB-A female/female

Seal: Silicone

Transfer rate: 5 Gb/s

Current: 2 A

Voltage: 5 V

Charging: yes

Protection rating: IP68

Temperature resistance: -25 °C to +105 °C

Cable diameter: 1.5–4.5 mm, 4.5–7.5 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950