



InLine 76619K interface cards/adapters Internal PCI



Model: 76619K

Manufacturer: INLINE

EAN: 4043718348336

Product Code: 1081901

R1,562

Adds two classic PCI slots to modern systems: Ideal for continuing to use proven PCI expansion cards in new PC or industrial systems.

Reliable signal transmission via connection cable: 60 cm long cable connects PCIe main card with add-on card and ensures stable data communication.

Flexible power supply via SATA 15-pin connector: Power supply directly to the main card – no additional adapter required.

Driverless installation for maximum compatibility: Operating system automatically recognizes the card – no manual setup required.

ASMedia bridge chip for high compatibility: The integrated ASM1083 chipset ensures stable PCIe-to-PCI conversion even under older operating systems.

With the InLine® interface card, PCIe x1 to 2x PCI 32-bit, you can expand modern computers with two classic PCI slots. The system consists of a PCIe main card with ASMedia ASM1083 bridge chip and an add-on card connected via a 60 cm cable. This makes the card ideal for continuing to use

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

older but functionally relevant PCI expansion cards – for example, in industrial PCs, test systems, or special applications where PCIe is not a substitute.

The card is driverless and compatible with a wide range of operating systems, including all Windows versions from XP onwards and Linux kernels from version 2.4 onwards. Power is supplied via a standardized SATA 15-pin connector, which allows for easy integration into existing setups. The PCI signals are reliably transmitted to the add-on card via the connection cable, which has two 32-bit slots.

Whether in a professional environment or in ambitious DIY projects, this solution offers a high-quality and durable way to continue using proven PCI hardware – without compromising on system updates.

Technical data

PCIe standard: PCIe v1.1 x1 lane (connection to the main card)

Interfaces: 2× PCI 32-bit, 33/66 MHz (provided on the add-on card)

Chipset: ASMedia ASM1083 (PCIe-to-PCI bridge)

Power supply: SATA 15-pin power connector on the main card

Driver: No driver installation required

Supported operating systems

Windows XP / Vista / 7 / 8 / 8.1 / 10 / 11 (32/64-bit)

Windows Server 2003 / 2008 / 2012 / 2016

Linux kernel 2.4 or newer

Scope of delivery

1x InLine PCIe x1 to 2× PCI interface card (main card, with PCIe plug-in card)

1x Add-on card with 2× PCI slots

1x 60 cm connection cable between main card and add-on card

1x SATA 15-pin power cable (approx. 5 cm)

1x User manual German/English

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950