



InLine 76625E interface cards/adapters Internal Parallel



Model: 76625E

Manufacturer: INLINE

EAN: 4043718341405

Product Code: 1081904

R1,151

Addition of a parallel DB25 port for connecting printers, scanners and other peripheral devices

PCIe x1 interface (compatible with x1, x4, x8 and x16 slots)

Bidirectional data transfer for efficient communication between devices

Supports SPP, EPP and ECP (IEEE 1284-compliant)

Low-profile format with low-profile slot bracket for compact systems

The **InLine® PCIe interface card** adds a powerful **25-pin parallel DB25 port** to your PC. It enables **reliable, bidirectional data transmission** and is ideal for connecting printers, scanners or other parallel port devices.

Thanks to the **PCI Express x1 interface (v1.1)**, the card is **compatible with x1, x4, x8 and x16 slots** and can be easily integrated into modern computer systems. The **256-byte FIFO buffer** ensures smooth and fast transfer with a data transfer rate of **up to 1.5 MB/s**.

Technical data:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Bus type & PCIe: PCIe v1.1 (2.5 GT/s) x1 lane (compatible with x1, x4, x8, x16 slots)

Connector: 1 x 25-pin parallel connector (DB25)

Chip set: WCH CH382L

Duplex mode: Bidirectional transmission

FIFO buffer: 256 bytes

Form factor: Low Profile

Dimensions: 85 mm x 60 mm (PCIe board)

Supported protocols & compatibility:

IEEE 1284 compliant, supports SPP, EPP and ECP

Data transfer rate:

Up to 1.5 MB/s - efficient, bidirectional LPT data transfer

Operating system support:

Windows: 11, 10, 8, 7, Vista, XP

Windows Server: 2003, 2008

Linux: from kernel version 2.4

Environmental conditions:

Operating temperature: 0 °C to 55 °C

Storage temperature: -40 °C to 70 °C

Maximum humidity: 90 %

Scope of delivery:

1x InLine® interface card, 1x parallel 25-pin, PCIe

1x low-profile slot bracket

1x driver CD

1x user manual (German/English)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Operating temperature: 0° C – 55° C

Storage temperature: -40° C – 70° C

Humidity: 10% - 90% non-condensing

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950