

InLine 76661M interface cards/adapter Internal USB 3.2 Gen 1 (3.1 Gen 1), USB Type-C

Model: 76661M

Manufacturer: INLINE

EAN: 4043718333691

Product Code: 1081916

R1,791

Triple USB expansion via PCIe: Two USB-A 3.2 Gen.1 ports and one USB-C port – ideal for mixed peripheral environments.

USB-C with Power Delivery 3.0: Up to 30 W charging power for smartphones, tablets and notebooks – right at your workstation.

High data rates up to 5 Gb/s: For fast file transfer and smooth operation of mass storage devices and USB devices.

6-pin PCIe power connector: Ensures stable power supply – even during intensive use.

Compatible with Windows & Linux: Broad system support, ideal for professional use in mixed infrastructures.

The InLine® 76661M interface card brings modern USB connectivity directly to your workstation,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

industrial PC or server environment. With two USB-A 3.2 Gen.1 ports and a full-featured USB-C port with Power Delivery 3.0 (30 W charging power), it is ideal for professional users with high demands on data transfer and power supply.
The USB-C port is not only suitable for data communication with modern devices such as docking stations, storage media or adapters – it also supplies power to power-intensive devices such as smartphones, tablets or ultrabooks. The two USB-A ports provide proven interfaces for classic USB peripherals.
The card is based on the stable VIA VL805 chipset, uses PCI Express V2.0 and is additionally powered via a 6-pin PCIe power connector to ensure stable voltage even under full port load.
It is compatible with all common operating systems from Windows XP and Linux from kernel 2.6.x. Ideal for technical workstations, media production, development environments or service providers who want to integrate modern USB technology into existing systems.

Chipset: VIA VL805
Interface: PCI Express V2.0
External connections: 2x USB-A 3.2 Gen.1, 1x USB-C 3.2 Gen.1 with PD3.0
Internal connection: 1x PCIe power (6-pin)
Data rates: 5 Gb/s, 480 Mb/s, 12 Mb/s, 1.5 Mb/s
Power: USB-C max. 30 W (20 V / 1.5 A), USB-A max. 4.5 W (5 V / 0.9 A)
Compatible operating systems: Windows XP or newer, Server 2008 R2 or newer, Linux from kernel 2.6.x
Operating temperature: 0° C – 55° C
Storage temperature: -40° C – 70° C
Humidity: 10% - 90% non-condensing

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950