



InLine 2+2ports USB 3.2 Gen.1 host controller, PCIe, w/SATA power + LP bracket

Model: 76666G

Manufacturer: INLINE

EAN: 4043718333226

Product Code: 1081918

R1,248

Four USB 3.2 Gen.1 ports via PCIe:Two external ports directly on the card, two via the included slot bracket – ideal for flexible connection solutions.

Low profile suitable:Includes matching slot bracket – for SFF systems and flat enclosures in industrial or office environments.

Up to 5 Gb/s data transfer rate:Super-fast access to peripherals such as SSDs, printers or scanners – even when used in parallel.

UASP support & backward compatibility:Compatible with USB Attached SCSI Protocol for faster storage access – including legacy USB support.

High compatibility with Windows & Linux:Universally applicable in workstations, workshops, technical rooms or embedded PCs.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The InLine® interface card 76666G expands professional systems with four USB 3.2 Gen.1 ports – two directly external and two via an enclosed slot bracket, which is connected via an internal 19-pin header. This makes the card ideal for applications with diverse USB requirements.

It is based on the reliable VIA VL805 chipset and offers a data transfer rate of up to 5 Gb/s – ideal for fast communication with peripheral devices such as SSDs, RAID systems, printers or cameras. Support for the USB Attached SCSI Protocol (UASP) further accelerates data transfer, which is particularly advantageous when using modern mass storage devices.

The card is PCIe V2.0-compatible and offers single-lane performance with high stability. It complies with both the USB 3.x specification Revision 1.0 and the USB 2.0 specification and supports legacy functions.

Thanks to its low-profile format, the card is perfect for compact enclosures, workstations and industrial applications. It is compatible with Windows XP and above, Windows Server 2008 R2 and above, and Linux systems with kernel 2.6.x and above – ideal for modern and mixed IT infrastructures.

Chipset: VIA VL805

Interface: PCI Express V2.0 (x1)

External connections: 2x USB-A 3.2 Gen.1 (direct)

Internal connections: 1x 19-pin USB 3.2 Gen.1 header (for 2x USB-A via slot bracket)

Slot bracket: Low-profile and standard included

Data rates: up to 5 Gb/s, backwards compatible

Protocol support: USB 3.x, USB 2.0, UASP, eXtensible Host Controller Interface

Compatible operating systems: Windows XP or newer, Server 2008 R2 or newer, Linux from 2.6.x

Operating temperature: 0° C – 55° C

Storage temperature: -40° C – 70° C

Humidity: 10% - 90% non-condensing

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950