



InLine 76666N interface cards/adapters Internal USB 3.2 Gen 2 (3.1 Gen 2)

Model: 76666N

Manufacturer: INLINE

EAN: 4043718347964

Product Code: 1081920

R1,184

Expansion with modern USB 3.2 interfaces:Upgrades desktop and industrial PCs with two additional USB-A 3.2 Gen. 2 ports for transfers of up to 10 Gb/s.

Stable power supply for powerful devices:The integrated SATA Power connection ensures a reliable power supply – ideal for external hard drives or docking stations.

Compatible and flexible:Supports Windows (7-11, 32 & 64 bit) and Linux from version 3.0 and fits in PCIe x4, x8, and x16 slots.

Easy installation without additional drivers:Plug & Play and hot-plugging enable quick use without complex configuration.

Compact design for various cases:The included low-profile slot bracket allows use even in small PC cases or industrial systems.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The InLine® interface card expands existing systems with two powerful USB-A 3.2 Gen. 2 ports with a transfer rate of up to 10 Gb/s. It is ideal for workstations or industrial environments where a reliable and fast data connection is required. Thanks to the ASMedia ASM1142 chipset, stable performance is ensured, even with high data loads.

The integrated SATA power connection also allows power-intensive devices such as external hard drives or docking stations to be operated reliably. The card supports Plug & Play and Hot Plug, enabling easy integration into existing systems without the need to install additional drivers. The low-profile slot bracket also makes it suitable for compact enclosures, offering flexible application options in professional environments.

The InLine® interface card offers a reliable solution for expanding workstations or servers with modern USB ports and ensures that your systems remain powerful in the future.

Chipset: ASMedia ASM1142

PCIe standard: PCIe v3.0 x4 lane

Supported operating systems: Linux v3.0 or higher, Windows 7/8/8.1/10/11 (32 & 64 bit)

UASP support: Yes

Max. current per port: 5 V / 900 mA (with SATA power)

Transfer rates: 10 Gb/s (USB 3.2 Gen. 2), 5 Gb/s (USB 3.2 Gen. 1), 480 Mb/s (USB 2.0)

Operating temperature: 0 °C to +85 °C

Storage temperature: -25 °C to +85 °C

Card length (without slot bracket): approx. 80 mm

Power supply: SATA power (optional)