



InLine 92501D wire connector Terminal block / D-Sub 9 Black, Green



Model: 92501D

Manufacturer: INLINE

EAN: 4043718345885

Product Code: 1081928

R820

Time savings during installation:Fast wiring via screw terminals for 18-24 AWG – tool-assisted with flat-head screwdriver ≤ 2 mm.

Stable connection thanks to screw lock:The D-Sub-9 connector is equipped with an integrated screw lock and ensures a secure mechanical connection to the matching socket – even in the event of vibration or movement.

Versatile use in industry:Ideal for automation, machine and plant engineering, control cabinet installations, and mobile test and service applications.

Compact design: The terminal block can be easily integrated even in limited space – whether on a DIN rail or in mobile units.

High signal quality:An insulation resistance of ≥ 10 M Ω at 300 V DC and a rated current of 1 A per pin ensure reliable signal transmission – even in continuous industrial applications.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The InLine® terminal block with D-Sub 9 connector and screw terminal connections was developed for professional use in serial signal wiring. The screw terminals with a 3.96 mm pitch enable secure connection of single wires in the 18-24 AWG range. They are operated using a standard flat-blade screwdriver with a blade width ≤ 2 mm.

The integrated screw lock ensures a stable connection to matching D-Sub sockets – even with vibration or frequent plugging. The EVA insulation layer on the underside provides additional protection when mounting on conductive surfaces. The compact design makes this terminal block a practical, durable solution for industrial applications where reliability, flexibility, and ease of use are required.

D-Sub 9 connector: With integrated screw lock

Connection technology: Screw terminal, pitch 3.96 mm

Connection range: 18-24 AWG

Actuation: With flat-blade screwdriver ≤ 2 mm

Rated current: 1 A per pin

Max. operating voltage: 100 V between two signals

Insulation resistance: ≥ 10 M Ω @ 300 V DC

Operating temperature: -10°C to +70°C

Insulation layer: EVA insulation on underside

Dimensions: approx. 38 × 37 × 16 mm (L × W × H)