



InLine 92501E wire connector Terminal block / D-Sub 9 Black, Green



Model: 92501E

Manufacturer: INLINE

EAN: 4043718345892

Product Code: 1081929

R820

Time savings during installation: Quick wiring via screw terminals for 12-22 AWG – tool-assisted with flat-head screwdriver ≤ 2.5 mm.

Stable connection thanks to screw lock: The D-Sub-9 socket is equipped with an integrated screw lock and ensures a secure mechanical connection to the matching socket – even in the event of vibration or movement.

Versatile use in industry: Ideal for automation, machine and plant engineering, control cabinet installations, and mobile test and service applications.

Compact, 2-row design: Measuring $45.5 \times 31 \times 16$ mm, the terminal block offers a space-saving arrangement – especially in dense wiring of Sub-D interfaces.

High signal quality: An insulation resistance of ≥ 10 M Ω at 300 V DC and a rated current of 1 A per pin ensure reliable signal transmission – even in continuous industrial applications.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The InLine® terminal block with D-Sub 9 socket in a 2-row design is designed for professional wiring solutions in control cabinet and device construction. The screw terminals with a 5.0 mm pitch enable the secure connection of single wires in the 12–22 AWG range. Assembly is tool-assisted using a flat-blade screwdriver with a blade width ≤ 2.5 mm.

The D-Sub socket can be securely screwed to the mating connector via an integrated screw lock, thus ensuring a vibration-proof connection. An EVA insulating layer provides protection when mounting on conductive surfaces. The compact 2-row design makes the connection block particularly suitable for industrial installations with high packing density – e.g., in control cabinets, machines, or mobile service units.

D-Sub 9 socket: 2-row, with integrated screw lock

Connection technology: Screw terminal, 5.0 mm pitch

Connection range: 12–22 AWG

Actuation: With flat-blade screwdriver ≤ 2.5 mm

Rated current: 1 A per pin

Max. operating voltage: 100 V between two signals

Insulation resistance: ≥ 10 M Ω @ 300 V DC

Operating temperature: -10°C to $+70^{\circ}\text{C}$

Insulation layer: EVA insulation on underside

Dimensions: approx. 46 × 31 × 18 mm (L × W × H)