




InLine 92502D wire connector Terminal block / D-Sub 15 Green



Model: 92502D

Manufacturer: INLINE

EAN: 4043718346011

Product Code: 1081941

R1,151

Time savings during installation:Quick wiring via screw terminals for 16–24 AWG – tool-assisted with flat-head screwdriver ≤ 2.5 mm.

Stable connection thanks to screw lock:The 2-row D-Sub-15 connector is equipped with a mounting thread (UNC #4-40) and enables secure mechanical fixation with matching sockets.

Versatile use in industry:Ideal for serial control lines in control cabinets, test benches, control systems, or building automation.

DIN rail mounting for structured installations:The robust DIN rail housing allows direct mounting on mounting rails – standard-compliant, secure, and space-saving.

High signal quality:An insulation resistance ≥ 10 M Ω at 300 V DC and a rated current of 1.0 A per pin ensure reliable signal transmission – even under continuous load.

The InLine® D-Sub 15 terminal block with connector in a 2-row design is ideal for structured wiring in control cabinets. Individual wires in the 16–24 AWG range can be connected quickly and securely via the side-accessible screw terminals with pressure plate. Tool-assisted wiring is carried out with a

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

flat-head screwdriver ≤ 2.5 mm.

The integrated screw lock (UNC #4-40) ensures a secure connection with matching sockets – vibration-proof and durable. The compact design and pre-assembled DIN rail clip enable quick and standard-compliant top-hat rail mounting in industrial environments.

D-Sub 15 connector: 2-row, with mounting thread for connector locking (UNC #4-40)

Connection technology: Screw terminal with pressure plate

Connection range: 16–24 AWG

Actuation: With flat-blade screwdriver ≤ 2.5 mm

Rated current: 1 A per pin

Max. operating voltage: 100 V between two signals

Insulation resistance: ≥ 10 M Ω @ 300 V DC

Operating temperature: -10 °C to $+70$ °C

Insulation layer: EVA insulation on underside

Mounting: Housing for direct mounting on DIN rail

Dimensions: approx. $87 \times 53 \times 51$ mm (L $\times$ W $\times$ H)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950