



InLine 92504D wire connector Micro USB / Terminal block, 5-pin Black, Green

Model: 92504D

Manufacturer: INLINE

EAN: 4043718346134

Product Code: 1081950

R958

Time savings during installation: Quick wiring via screw terminals for 16-26 AWG – tool-assisted with flat-head screwdriver ≤ 2.5 mm.

Integrated USB cable for flexible applications: The 1-meter connection cable connects systems immediately – without additional accessories or soldering.

Clear terminal assignment & secure contact: 5-pin terminals with pressure plate, clearly labeled 1: –, 2: D+, 3: D–, 4: +, 5: S (shield) – ideal for service, testing, and prototyping.

Versatile use in industry: For fast connection of USB 2.0 signals in test setups, laboratories, commissioning, or troubleshooting – without soldering.

High signal quality: An insulation resistance of ≥ 10 M Ω at 300 V DC and a rated current of 0.7 A per pin ensure reliable signal transmission – even under continuous load and in industrial environments.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The InLine® Micro USB 2.0 terminal block adapter with 5-wire connection cable combines the advantages of a stable USB connection with the flexibility of open signal wiring. The mini USB socket is permanently connected to a 5-pin screw terminal block – ideal for test benches, diagnostic devices, or embedded systems.

The screw terminals are clearly labeled (1: ground, 2: D+, 3: D-, 4: voltage, 5: shield) and enable secure and unambiguous signal assignment. The terminal connections with a 5.0 mm grid size support wires in the range of 16–26 AWG. Wiring is tool-assisted with a flat-head screwdriver ≤ 2.5 mm.

The integrated 1-meter connection cable reduces wiring effort and allows immediate use – e.g., on control systems, test systems, or mobile test stations. An EVA insulating layer on the underside provides additional protection when mounting on conductive surfaces.

USB interface:Micro USB 2.0, female connector

Cable length:approx. 1 m (PVC, permanently integrated)

Number of pins / assignment:5 terminals / 1: – / 2: D+ / 3: D- / 4: + / 5: S

Connection technology:Screw terminal with pressure plate, 5.0 mm grid

Connection range:16–26 AWG

Actuation:With flat-blade screwdriver ≤ 2.5 mm

Rated current: 0.7 A per pin

USB operating voltage (VBUS):5 V DC

Test voltage (insulation resistance):300 V AC / 1 minute

Insulation resistance: $\geq 10 \text{ M}\Omega$ @ 300 V DC

Operating temperature:–20 °C to +105 °C

Insulation layer:EVA insulation on underside

Dimensions:Terminal block approx. 50 × 21.2 × 18.4 mm (L × W × H)