




InLine 92505C wire connector 2x RJ45 8P8C / 2x Terminal block 9 terminals Green

Model: 92505C

Manufacturer: INLINE

EAN: 4043718346271

Product Code: 1081963

R1,216

Time savings during installation: Two screw terminal strips for 8 wires plus shielding each enable fast, solder-free wiring – tool-assisted with a flat-head screwdriver ≤ 2.5 mm, suitable for 16–26 AWG.

Dual RJ45 interface with separate signal routing The two standardized RJ45 sockets (8P8C) in a straight design are independently connected – ideal for parallel cable routing, redundancy solutions, or testing purposes.

DIN rail mounting for orderly system integration: Robust housing with pre-mounted DIN rail clip – ideal for structured network and control cabling in control cabinets.

Versatile use in industry: Suitable for Ethernet signal distribution, machine communication, embedded projects, or network diagnostics in test environments.

High signal quality: An insulation resistance of ≥ 10 M Ω at 300 V DC and a rated current of 1.0 A

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

per pin ensure reliable and secure data transmission – even under continuous load in industrial environments.

The InLine® terminal block with **two RJ45 sockets (8P8C, straight version)** and separate terminal assignment was developed for structured network connections in control cabinets, test environments, or embedded systems.

Both sockets are completely independently connected to a **screw terminal strip with 9 connections** (8 signals + shield) – ideal for parallel signal routing, redundancy solutions, or comparative measurements.

The terminal strips (5.0 mm pitch) support single wires in the 16–26 AWG range and can be wired with a flat-blade screwdriver ≤ 2.5 mm.

Thanks to the pre-mounted DIN rail clip, the module is immediately ready for standard-compliant integration into common mounting rail systems.

The robust design, well-thought-out signal routing, and tested short-circuit and miswiring protection make the adapter the ideal choice for demanding industrial Ethernet applications.

RJ45 interface: 2x 8P8C socket (straight design)

Screw terminal strip: 2x 9 terminals (8 signals + shield), 5.0 mm pitch, with pressure plate

Connection range: 16–26 AWG

Actuation: With flat-head screwdriver ≤ 2.5 mm

Rated current: 1.0 A per pin

Max. operating voltage: 100 V between two signals

Insulation resistance: ≥ 10 M Ω @ 300 V DC

Operating temperature: -20 °C to +70 °C

Insulation layer: EVA insulation on underside

Mounting: Prepared for DIN top-hat rail

Dimensions: approx. 60 × 90 × 19 mm (W × H × D)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950