

Neewer Q6 Flash



Model: 10105859

Manufacturer: NEEWER

EAN: 6921268813772

Product Code: 1088022

R10,956

Neewer Q6 Flash

The NEEWER Q6 is a 600Ws flash that is ideal for both outdoor and studio photography. It offers a very fast recycle time ranging from 0.01 to 0.9 seconds, HSS synchronization up to 1/8000 second, and a stable color temperature of 5800K. Thanks to its 28.8V battery, it can fire up to 400 full-power flashes, and the built-in 30W LED light can serve as a continuous light during video recording.

Precise light control and fast flash

The flash allows power adjustment from 1/512 to full power (1/1) in 0.1-stop increments, making it easy to tailor the light to a specific scene. A short flash duration—up to 1/7633 s—allows you to effectively freeze motion, making this model ideal for sports photography, dynamic portraits, or outdoor work. A constant color temperature minimizes the risk of color shifts between shots, reducing the need for post-processing.

TTL, Manual, and Stroboscopic Modes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The NEEWER Q6 is compatible with Canon E-TTL II, Nikon i-TTL, Sony TTL, and Fujifilm TTL systems. The available TTL, Manual, and Stroboscopic modes allow you to adapt the flash's operation to different photography styles. Multi mode supports a frequency of up to 100 Hz and up to 100 flashes, enabling you to capture impressive action shots. The flash also supports first- and second-curtain sync and HSS for shooting with fast shutter speeds.

Advanced 2.4G Wireless System

The built-in Neewer Q System allows operation in both transmitter and receiver modes and controls flashes from a distance of up to 100 meters. Support for 32 channels, 5 groups, and IDs makes it easier to organize more complex lighting setups. The model is also compatible with the Godox 2.4G X system and the Sekonic L-858D light meter, making it easier to integrate with your existing photography gear.

LED light for photos and video

The built-in 30W LED modeling light offers color temperature adjustment from 2700K to 6500K. Thanks to high CRI 95+ and TLCI 98+ ratings, the light accurately renders colors, making it suitable not only for previewing lighting setups but also as an additional light source during video recording. The standard Bowens mount allows for the use of popular softboxes, reflectors, and other light modifiers.

Convenient operation and portable design

The NEEWER Q6 is equipped with two color TFT displays featuring an easy-to-read interface and color-coded labels, making it easy to quickly adjust settings while working. A built-in fan helps maintain stable operation during intensive use, and a sturdy carrying handle improves the convenience of transporting the equipment. The ability to control the light via a mobile app further streamlines operation during shoots in larger spaces.

Included

- 1 x Q6 Outdoor Light
- 1 x Standard Reflector

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- 1 x Lithium Battery
- 1 x Hot Tube Cover
- 1 x Carrying Handle
- 1 x Power Cable
- 1 x Power Adapter
- 1 x Carrying Case (Case)

Manufacturer	NEEWER
Model	Q6
Power	600Ws
Color temperature	5800K (+/-150K)
Number of full-power flashes	400 (with modeling light off)
Flash duration	max. 1/7633s
Recycle time	approx. 0.01-0.9s
Flash modes	TTL / M / MULTI / BURST MODE
Stroboscopic flash	1-100Hz, 1-100 flashes
Flash exposure compensation (FEC)	-3EV to +3EV in 1/3 EV steps
Sync modes	High Speed Sync (HSS), front-curtain / rear-curtain
Flash delay	0.01-30 s
Masking function	Yes
Built-in silent fan	Yes
Built-in beeper	Yes
Flash duration display	Yes
2.4G wireless system	32 channels, 5 groups (A, B, C, D, E)
2.4G transmission range	100 m
Modeling light (LED)	30W / 2700K-6500K / CRI 95+
Triggering methods	2.4G, S1/S2 photocell, 3.5mm sync socket

Power supply Lithium battery, AC adapter (Dummy Battery)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Energy saving

Option to set automatic shutdown after 30-120 minutes of inactivity

Display

Two color screens

Dimensions (without handle)

195 x 185 x 170 mm

Weight (without handle)

3 kg

GPSR Link: <https://psr->

assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photo_accessories.pdf, Gross weight: 5580, Net weight: 3574, Box length: 34,50, Box width: 31,50, Box height: 21,50

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950