

Neewer Z2-N TTL Speedlite Flash for Nikon Cameras



Model: 10104958

Manufacturer: NEEWER

EAN: 6921268814465

Product Code: 1088030

R4,178

Neewer Z2-N TTL Speedlite Flash for Nikon Cameras

The Neewer Z2-N is designed to work with Nikon cameras, offering automatic TTL metering, manual mode, and stroboscopic flash. Thanks to HSS synchronization up to 1/8000s, you can comfortably shoot in full sunlight without having to sacrifice fast lenses and shallow depth of field. The TCM function allows you to quickly switch from TTL to manual mode while retaining the previously selected flash power.

Even light and a swivel head

The round head design generates softer and more natural light than standard reporter lights. The 76Ws power output works well for both portrait and reportage photography. The head rotates 330° and tilts from -7° to 120°, making it easy to bounce light and create more natural scene lighting.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

LED Modeling Light

Two 2W dimmable LEDs help you assess the lighting setup before taking the shot. The 10-step adjustment allows you to tailor the light intensity to your shooting conditions, making it easier to focus and plan shadows and highlights.

Fast Performance and Efficient Battery

The built-in lithium battery provides up to 600 full-power flashes and a fast recycle time of approximately 1.5 seconds. These specifications are ideal for dynamic shoots and event photography, where quick equipment response times are critical.

2.4G wireless communication

The flash supports the Neewer 2.4G system with a range of up to 100 meters. The ability to operate as a Master or Slave, along with support for multiple groups and channels, allows for convenient control of an extensive flash setup. Compatibility with the Godox X system further expands integration possibilities with other photography equipment.

Compatibility with Nikon Cameras

This model is compatible with many Nikon cameras, including the Z9, Z8, Z6 II, Z7 II, D850, D780, D750, and D7500. The flash is designed to work with both the Z-series mirrorless cameras and classic Nikon DSLRs.

Included in the set

- 1 × flash
- 1 × lithium battery
- 1 × USB Type-C cable
- 1 × stand (mini tripod)
- 1 × protective case
- 1 × user manual

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Manufacturer	NEEWER
Model	Z2-N
Product type	i-TTL flash
Compatibility	Nikon cameras (including Z9, Z8, Zfc, Z50, Z30, Z5, Z6, Z7, Z6II, Z7II, D4, D5, D6, D90, D200, D300, D610, D700, D750, D780, D800, D850, D3000 series, D5000 series, D7000 series; NOT COMPATIBLE with D810)
Flash power	76Ws
Zoom range	28-105 mm (automatic or manual)
HSS sync	up to 1/8000 s
Recycle time	approx. 1.5 s
Flash duration	1/180 s - 1/20000 s
Operating modes	i-TTL / Manual / Stroboscopic
Power adjustment range	1/1 - 1/256
Exposure compensation	yes
Photocell modes	S1 / S2
Wireless system	2.4G Q System / compatible with Godox 2.4G X System
Transmission range	up to 100 m (in open space)
Channels	32
ID	1-99
Master groups	A / B / C / D
Slave groups	A / B / C / D / E
LED modeling light	yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

LED brightness levels	10
LED color temperature	3300K $\pm$ 200K
Power supply	7.4V / 2600 mAh lithium battery
Battery capacity	approx. 480–600 flashes at full power
Head movement range	rotation 0°–330°, tilt –7° to 120°
Material	plastic
Dimensions	206 × 76 × 76 mm
Weight	580 g (with battery)

base_xml: 1, Gross weight: 1010, Net weight: 499, Box length: 24,00, Box width: 17,50, Box height: 10,00, Set: Yes, Adjustable intensity: Yes, GPSR Link: https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photographic_studio.pdf