

Neewer Z2-C TTL Speedlite Flash for Canon Cameras



Model: 10104956

Manufacturer: NEEWER

EAN: 6921268814458

Product Code: 1088031

R3,948

Neewer Z2-C TTL Speedlite Flash for Canon Cameras

The Neewer Z2-C is designed for Canon DSLR and mirrorless cameras, offering support for TTL, Manual, and Stroboscopic modes. The TCM function allows you to switch settings from automatic TTL metering to manual mode with a single button, which speeds up your workflow during photojournalism, portrait sessions, or event photography. The flash also supports HSS synchronization up to 1/8000s, allowing you to comfortably shoot in bright daylight with a wide aperture.

Round head and natural light

The round flash head provides a more even light distribution than traditional designs. The 76Ws power and stable color temperature of 5600K help achieve a natural look in photos both in and out

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

of the studio. The swivel head with 330° rotation and tilt from -7° to 120° makes it easy to bounce light off walls and ceilings, allowing for a softer effect without additional modifiers.

Dual LED modeling lights

The lamp is equipped with two 2W LED modeling lights with a color temperature of 3300K. The 10-level brightness adjustment helps you better assess the shadow pattern and makes it easier to focus before taking a photo. This solution works particularly well for portrait photography and when working in dimly lit rooms.

High-capacity battery and fast charging

The 7.2V/3000mAh lithium battery allows for up to 600 full-power flashes, and a recycling time of approximately 1.5 seconds enables you to work without long pauses between shots. The USB-C port allows for convenient charging and software updates, making it easier to maintain compatibility with new camera models.

2.4G Wireless System

The Neewer Z2-C works with a 2.4G wireless system, supporting 32 channels, 99 IDs, and groups A/B/C/D. The flash can operate as a Master or Slave unit, making it easy to expand your own lighting setup. Compatibility with the Godox X system and QPRO triggers expands configuration options during more complex photo shoots.

Compatibility with Canon Cameras

The model is compatible with many Canon cameras, including the R5, R6, R3, 5D Mark IV, 6D Mark II, 90D, 80D, and 7D Mark II. The design has been adapted to work with both DSLRs and select Canon mirrorless cameras.

Included in the set

- 1 × flash
- 1 × lithium battery

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- 1 × USB Type-C cable
- 1 × stand (mini tripod)
- 1 × protective case
- 1 × user manual

Manufacturer	NEEWER
Model	Z2-C
Product type	E-TTL II flash
Compatibility	Canon cameras (including R6, R5, R3, R, M6, 90D, 80D, 7D, 6D, 5D, 850D, 800D, 250D; NOT COMPATIBLE with RP and R50)
Flash power	76Ws
Zoom range	28-105 mm (automatic or manual)
HSS sync	up to 1/8000 s
Recycle time	approx. 1.5 s
Flash duration	1/180 s - 1/20000 s
Operating modes	E-TTL II / Manual / Stroboscopic
Power adjustment range	1/1 - 1/256
Exposure compensation	Yes (including FEB and FEL)
Photoelectric sensor modes	S1 / S2
Wireless system	2.4G Q System / compatible with Godox 2.4G X System
Transmission range	up to 100 m (in open space)
Channels	32
ID	1-99
Master groups	A / B / C / D
Slave groups	A / B / C / D / E

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

LED modeling light	Yes (two LEDs with a stable color temperature of 5600K $\pm$ 200K for the flash)
---------------------------	--

LED brightness levels	10
------------------------------	----

LED color temperature	3300K $\pm$ 200K
------------------------------	------------------

Power supply	7.4V / 2600 mAh lithium battery
---------------------	---------------------------------

Battery capacity	approx. 480–600 flashes at full power
-------------------------	---------------------------------------

Head movement range	rotation 0°–330°, tilt –7° to 120°
----------------------------	------------------------------------

Material	plastic
-----------------	---------

Dimensions	206 × 76 × 76 mm
-------------------	------------------

Weight	580 g (with battery)
---------------	----------------------

Gross weight: 950, Net weight: 499, Box length: 24,50, Box width: 14,00, Box height: 9,50, Set: Yes, Adjustable intensity: Yes, GPSR Link: https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photographic_studio.pdf

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950