

Uni-T UT161B Digital Multimeter



Model: UT161B

Manufacturer: UNI-T

EAN: 6935750516157

Product Code: 1089528

R2,115

Uni-T UT161B universal digital multimeter

The Uni-T UT151A is a practical digital multimeter designed for basic maintenance work, system inspections, and the diagnosis of electrical and electronic devices. The device measures AC/DC voltage up to 600 V, current up to 10 A, and resistance up to 200 MΩ, making it suitable for both simple home repairs and more demanding workshop tasks. The easy-to-read display with a maximum reading of 2000 facilitates quick reading of results, and the compact housing fits comfortably in the hand.

Features for ease of use and safety

The UT151A model is equipped with manual range selection, a Data Hold function, a continuity test, a diode test, and an hFE transistor test. An additional capacitance measurement jack streamlines work with capacitors, while auto-off and a low-battery indicator enhance the convenience of daily use. Compliance with safety categories CAT II 600V and CAT III 300V allows for safe performance of

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

typical electrical measurements.

Included

- Digital multimeter
- 4 AAA batteries
- Test leads
- USB cable
- User manual

Specifications

Manufacturer	Uni-T
Model	UT161B
Type	True RMS digital multimeter
DC voltage	1000V ±(0.5%+3)
AC Voltage	1000V ±(1.0%+3)
DC Current	10A ±(1.0%+2)
AC Current	10A ±(1.2%+5)
Resistance	60MΩ ±(1.0%+2)
Capacitance	60mF ±(3.0%+5)
Frequency	10 MHz ±(0.1%+4)
Duty cycle	0.1% ~ 99.9% ±(2.0%+5)
Maximum reading	6000
AC bandwidth	40 Hz ~ 500 Hz
Functions	True RMS, NCV, diode test, continuity test, Data Hold, Relative mode, Max/Min, backlight, bar graph, USB communication
Power supply	4x 1.5V AAA batteries
Dimensions	190 × 90 × 50 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Weight 350 g

Safety CAT III 1000V / CAT IV 600V

Certifications CE, UKCA, cETLus

GPSR Link: https://psr-assets.innpro.pl/tools/sg_tools_measuring_tools.pdf, Gross weight: 770, Net weight: 350, Box length: 22,00, Box width: 16,00, Box height: 7,50

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950