

Uni-T UT256A Multimeter



Model: UT256A

Manufacturer: UNI-T

EAN: 6935750525609

Product Code: 1089537

R1,715

Uni-T UT256A clamp meter

The Uni-T UT256A is a True RMS clamp meter that allows for convenient current measurement by placing the wire inside the open clamp. This design simplifies operation, eliminates the moving parts typical of clamp meters, and enhances comfort during daily use. The model can measure AC current up to 200 A, AC/DC voltage up to 1000 V, resistance up to 60 MΩ, and frequency from 10 Hz to 10 kHz, making it ideal for a wide range of service and diagnostic tasks.

Practical features and ease of use

A maximum reading of 6000, automatic range switching, and True RMS technology ensure convenient and accurate measurements. The device is equipped with an NCV function for non-contact voltage detection, as well as Data Hold, a continuity buzzer, an LCD backlight, automatic shut-off, and a low-battery indicator. Weighing 248 g and measuring 217 × 58.8 × 38.5 mm, the meter remains comfortable for everyday use, and compliance with safety categories CAT II 1000V and CAT III 600V enhances workplace safety

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Included

- Clamp meter
- Test leads (1 pair)
- 2 AA batteries (LR6)
- Carrying case
- User manual

Specifications

Manufacturer	Uni-T
Model	UT256A
Product type	True RMS digital clamp meter
AC current range	200 A ±(1.8% + 5)
AC voltage range	1000 V ±(1.2% + 3)
DC voltage range	1000 V ±(0.8% + 3)
Resistance measurement range	60 MΩ ±(1% + 2)
Frequency range	10 Hz – 10 kHz ±(0.1% + 5)
Maximum display reading	6000
Functions	True RMS, NCV, continuity test, Data Hold, auto-range, LCD backlight, auto-off, low battery indicator
Measurement category	CAT II 1000V / CAT III 600V
Power supply	2 × 1.5 V AA batteries (LR6)
Display dimensions	35 × 26 mm
Dimensions	217 × 58.8 × 38.5 mm
Weight	248 g
Certifications	CE, UKCA, cETLus

GPSR Link: https://psr-assets.innpro.pl/tools/sg_tools_measuring_tools.pdf, Gross weight: 430, Net weight: 248, Box length: 23,00, Box width: 10,50, Box height: 6,00