

Uni-T UT675A Battery Tester



Model: UT675A

Manufacturer: UNI-T

EAN: 6935750567500

Product Code: 1089541

R2,672

Uni-T UT675A battery tester

The Uni-T UT675A is a tester designed for the rapid diagnosis of automotive batteries and vehicle electrical systems without the need to remove the battery. The device supports lead-acid batteries with capacities ranging from 3 Ah to 250 Ah, including AGM, GEL, and EFB models, making it suitable for use in many types of vehicles. It enables the measurement of voltage and internal resistance, as well as the assessment of battery capacity and condition, allowing for the quick detection of potential issues. Additionally, the tester performs starting and charging system tests for 12 V and 24 V systems, expanding the diagnostic capabilities. The built-in printer and USB connectivity allow for the creation and archiving of measurement reports, which facilitates the documentation of results and daily work in a workshop or service center.

Included

- Battery tester
- USB cable

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Thermal paper roll (for printer)
- User manual

Specifications

Manufacturer	Uni-T
Model	UT675A
Product type	Battery tester with built-in printer
Battery voltage testing range	7-16 V DC
Starting system test	12 V / 24 V
Charging system test	12 V / 24 V
Supported battery types	Lead-acid, AGM, GEL, EFB
Battery capacity range	3-250 Ah
Test standards	CCA, BCI, CA, MCA, JIS, DIN, IEC, EN, SAE, AH
Measured parameters	Voltage, resistance, capacity, cycle life
Connectivity	USB
Built-in printer	Yes
Display type	128 × 64 LCD display
Power supply	From the tested vehicle battery
Dimensions	95 × 47 × 183 mm
Weight	413 g
Certifications	CE, UKCA, FCC

GPSR Link: https://psr-assets.innpro.pl/tools/sg_tools_measuring_tools.pdf, Gross weight: 960, Net weight: 413, Box length: 27,50, Box width: 23,00, Box height: 9,00