

Uni-T UT311A Vibration Tester



Model: UT311A

Manufacturer: UNI-T

EAN: 6935750531136

Product Code: 1089563

R5,950

Uni-T UT311A Vibration Tester

The Uni-T UT311A Vibration Tester is a compact machine condition monitoring device that measures vibration acceleration, velocity, and displacement with instant readings displayed on a 2.4" TFT screen. The device operates in two frequency modes for acceleration (LO: 10 Hz-1 kHz and HI: 1 kHz-15 kHz), allowing you to tailor the measurement to the nature of the equipment's operation. Its compact design, auto-rotating screen, built-in flashlight, and USB-C rechargeable battery make the UT311A ideal for field inspections and routine diagnostics of industrial equipment.

Measurements tailored to various applications

The UT311A offers three key measurement methods: acceleration (PEAK), velocity (RMS), and displacement (P-P), allowing you to assess both dynamic vibrations and the overall operating condition of the machine. Separate frequency modes for acceleration (LO and HI) allow for more precise analysis of both slower and faster vibrations, rather than using a single generalized range. The Data Hold function allows you to freeze the result on the screen, making it easier to read in less

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

convenient conditions. The 1350 mAh battery provides up to approximately 12 hours of operation, and charging via USB-C takes about 3 hours. The weight of approximately 191 g refers to the device together with the short probe, i.e., in a ready-to-use configuration.

Included

- Uni-T UT311A Vibration Tester
- Long measurement probe
- Short measurement probe
- USB-C charging cable
- User manual
- Safety instructions

Manufacturer	Uni-T
Model	UT311A
Acceleration measurement	0.1-199.9 m/s²
Velocity measurement	0.1-199.9 mm/s
Displacement measurement	0.001-1.999 mm
Acceleration frequency range	LO 10 Hz-1 kHz / HI 1 kHz-15 kHz
Velocity frequency range	10 Hz-1.5 kHz
Displacement frequency range	10 Hz-1 kHz
Resolution	0.1 m/s² / 0.1 mm/s / 0.001 mm
Acceleration and velocity accuracy	±(5%+2 digits)
Displacement accuracy	±(10%+2 digits)
Display	2.4" TFT LCD, auto-rotation, backlight
Functions	Data Hold, flashlight, battery indicator, auto power off after 5 min
Power supply	1350 mAh Li-Ion battery, 3.7 V
Charging	USB-C, DC 5 V

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Operating time	approx. 12 h
Operating conditions	0°C–40°C, ≤80% RH (non-condensing)
Dimensions	180 × 28 × 64 mm (with short probe)
Weight	191 g (with short probe)

GPSR Link: https://psr-assets.innpro.pl/tools/sg_tools_measuring_tools.pdf, Gross weight: 730, Net weight: 230, Box length: 27,50, Box width: 21,50, Box height: 9,00