

Uni-T UT303C+ Infrared Thermometer



Model: UT303C+

Manufacturer: UNI-T

EAN: 6935750530375

Product Code: 1089565

R2,996

Uni-T UT303C+ Infrared Thermometer

The Uni-T UT303C+ infrared thermometer is an advanced device for non-contact surface temperature measurement over a wide range from -32°C to 1300°C , equipped with an innovative ring laser pointer that precisely marks the entire measurement area. The model offers a fast response time of 250 ms and high accuracy of $\pm 1.5^{\circ}\text{C}$ or $\pm 1.5\%$ for temperatures $\geq 0^{\circ}\text{C}$, while for sub-zero temperatures, the error is calculated using the formula $\pm(1.5^{\circ}\text{C} + 0.1^{\circ}\text{C}/^{\circ}\text{C})$. The device features adjustable emissivity (0.1–1.0), a clear color EBTN display, measurement analysis functions (MAX/MIN/AVG/DIFF), and the ability to store up to 99 results with date and time, making it a precise tool for temperature control without contact with the object being tested.

Functionality and Measurement Precision

The Uni-T UT303C+ was designed for maximum accuracy and ease of use—thanks to its 30:1 D:S ratio, it enables measurements from a greater distance while maintaining high precision. A unique

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

ring laser allows for precise definition of the measurement field, which significantly facilitates work in demanding conditions. The device offers visual and audible alarms, a HOLD function, data logging, and the ability to perform scheduled measurements. Its ergonomic design, backlight, and drop resistance from heights of up to 1 meter enhance the comfort of daily use.

Included

- Uni-T UT303C+ Infrared Thermometer
- 9V battery
- Carrying case
- User manual
- Blister packaging
- Manufacturer’s packaging

Manufacturer	Uni-T
Model	UT303C+
Temperature measurement range	-32°C ~ 1300°C
Repeatability	0.7°C or 0.7%
D:S ratio	30:1
Response time	250 ms
Emissivity adjustment	0.1 – 1.0 (5 presets)
Spectral range	8–14 μm
Laser	Ring Laser
Display	color EBTN
Measurement modes	MAX / MIN / AVG / DIFF / HOLD
Measurement memory	up to 99 records (with date and time)
Alarms	visual + audible
Operating temperature	0°C ~ 50°C
Storage temperature	-20°C ~ 60°C
Operating humidity	90% RH (non-condensing)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Drop test	1 m
Power supply	9V battery
Weight	310 g
Dimensions	172 x 113.5 x 53 mm
Tripod mount	Yes

GPSR Link: https://psr-assets.innpro.pl/tools/sg_tools_measuring_tools.pdf, Gross weight: 470, Net weight: 310, Box length: 14,50, Box width: 7,50, Box height: 23,50

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950