

Uni-T UT302D+ Infrared Thermometer



Model: UT302D+

Manufacturer: UNI-T

EAN: 6935750530290

Product Code: 1089567

R1,995

Uni-T UT302D+ Infrared Thermometer

The Uni-T UT302D+ infrared thermometer is an advanced device for non-contact surface temperature measurement in the range of -32°C to 1100°C , equipped with a dual laser for precise targeting. It offers a fast response time of 250 ms and high accuracy of $\pm 1.5^{\circ}\text{C}$ or $\pm 1.5\%$ for temperatures $\geq 0^{\circ}\text{C}$, while for sub-zero temperatures, the error is calculated using the formula $\pm(1.5^{\circ}\text{C} + 0.1^{\circ}\text{C}/^{\circ}\text{C})$. The model features adjustable emissivity (0.1–1.0), a clear color EBTN display, and measurement analysis functions (MAX/MIN/AVG/DIFF), making it an effective tool for fast and accurate temperature control.

Advanced functionality and data management

The Uni-T UT302D+ offers extensive capabilities thanks to features such as storage of up to 99 measurements with date and time, visual and audible alarms, and a scheduled measurement option. A 20:1 D:S ratio enables convenient non-contact measurements with the precision typical of the

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

UT302 series, while the ergonomic design and backlight enhance user comfort. A rugged housing resistant to drops from heights of up to 1 meter ensures the device performs well in a variety of conditions.

Included

- Uni-T UT302D+ Infrared Thermometer
- 9V battery
- Carrying case
- User manual
- Blister packaging
- Blister packaging

Manufacturer	Uni-T
Model	UT302D+
Temperature measurement range	-32°C ~ 1100°C
Repeatability	0.7°C or 0.7%
Distance-to-Spot Ratio (D:S)	20:1
Response time	250 ms
Emissivity adjustment	0.1 – 1.0 (5 presets)
Spectral range	8–14 μm
Laser	Dual Laser
Laser power	1 mW
Display	color EBTN (35 x 35 mm)
Measurement modes	MAX / MIN / AVG / DIFF
Measurement memory	up to 99 entries (with date and time)
Alarms	visual + audible
Operating temperature	0°C ~ 50°C
Storage temperature	-20°C ~ 60°C

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Operating humidity	90% RH (non-condensing)
Drop test	1 m
Power supply	9V battery
Weight	310 g
Dimensions	172 x 113.5 x 53 mm
Tripod mount	Yes

GPSR Link: https://psr-assets.innpro.pl/tools/sg_tools_measuring_tools.pdf, Gross weight: 470, Net weight: 310, Box length: 21,00, Box width: 14,00, Box height: 7,50

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950