



InLine 17925X HDMI cable 25 m HDMI Type A (Standard) Black



Model: 17925X

Manufacturer: INLINE

EAN: 4043718343263

Product Code: 1097578

R1,624

High transmission quality over long distances: Hybrid cable technology combines fibre optics and copper for loss-free 8K/4K signal transmission up to 50 m.

Future-proof thanks to HDMI 2.1 support: Transmits up to 48 Gb/s and supports 3D, Dynamic HDR, eARC and 240 Hz - ideal for current and upcoming AV standards.

Rugged aluminium connectors: High-quality workmanship with gold-plated contacts for stable, long-lasting connections in professional installations.

Compact cable diameter: With an outer diameter of just 4.8 mm, it can be laid flexibly, even in tight cable ducts and wall openings.

Directional for stable signal quality: Clear labelling of the signal direction ensures error-free installation and maximum performance.

The InLine® HDMI AOC cable series is the ideal solution for professional applications where the highest signal quality is required, even over long distances. Thanks to the combination of four fibre optic cores and seven copper strands, these hybrid cables offer uncompromising transmission of

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

8K/4K video signals with a bandwidth of up to 48 Gb/s. All current HDMI 2.1 standards such as Dynamic HDR, eARC, 3D or 240 Hz are reliably supported.

The cables are designed to be directional to ensure maximum signal stability - clearly indicated by the labelling on the connectors (source/display). Robust aluminium connectors with gold-plated contacts ensure long-lasting connections in demanding AV installations. Thanks to the narrow cable diameter of just 4.8 mm and the flexible PVC sheathing, the AOC cables can be laid easily and save space - ideal in conference rooms, digital signage applications or technical centres.

Rely on modern connection technology that makes no compromises, even over longer distances.

Hybrid cable consisting of 4 fibre optic and 7 solid copper strands

Directional signal cable: HDMI plug (source) to HDMI plug (display)

Cable: Ø 4.8 mm, PVC-sheathed

Max. Data transfer rate: 48 Gb/s (12 Gb/s per channel)

Supports 3D, HDCP, EDID, CEC, DDC, Dynamic HDR, eARC, ARC and other specifications according to HDMI