

Lanberg NC- 1200-WIE network card Internal WLAN 1200 Mbit/s



Model: NC-1200-WIE

Manufacturer: LANBERG

EAN: 5901969438673

Product Code: 1099631

R862

Maximum data transfer rate: 1200 Mbit/s | LAN controller: Realtek RTL8812BU | Operating relative humidity (H-H): 10 - 90% | Frequency range: 2.4 - 5 GHz | Antenna gain level (max): 5 dBi | Connectivity technology: Wireless | Weight: 24 g | Security algorithms: WPA-PSK | Networking standards: IEEE 802.11e | Networking standards: IEEE 802.11n | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Security algorithms: WPS-PBC | Networking standards: IEEE 802.11ac | Operating temperature (T-T): 0 - 40 °C | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11i | Security algorithms: WPS | Security algorithms: WPA | Security algorithms: WPS-PIN | Networking standards: IEEE 802.11k | Security algorithms: WMM | Security algorithms: WPA2-PSK | Antenna type: 2x2 | Security algorithms: 128-bit WEP | Modulation: 64-QAM | Modulation: DSSS | Modulation: 256-QAM | Product colour: Black | Modulation: DQPSK | Modulation: DBPSK | Component for: PC | Modulation: QPSK | Security algorithms: WEP | Modulation: CCK | Modulation: OFDM | Modulation: 16-QAM | Modulation: BPSK | Warnings: Before use, make sure the device is correctly

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

connected to the USB port. | Warnings: Protect the device from moisture and extreme temperatures.
| Warnings: Do not disassemble or modify the device to avoid damage or electric shock. | USB
powered: Yes | Windows operating systems supported: Windows Vista x64 | Windows operating
systems supported: Windows 11 | Wi-Fi standards: Wi-Fi 5 (802.11ac) | USB connector form factor:
Straight | Mac operating systems supported: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | USB version:
3.2 Gen 1 (3.1 Gen 1) | Windows operating systems supported: Windows 8 x64 | Windows operating
systems supported: Windows XP | Windows operating systems supported: Windows Vista | Windows
operating systems supported: Windows 7 x64 | Windows operating systems supported: Windows 8 |
Height: 10.3 mm | Antenna design: External | Windows operating systems supported: Windows 7 |
Windows operating systems supported: Windows 10 x64 | Host interface: USB | Top Wi-Fi standard:
Wi-Fi 5 (802.11ac) | Windows operating systems supported: Windows 10 | Wi-Fi: Yes | Chipset:
RTL8812BU | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Linux operating systems supported: Yes |
Width: 20.5 mm | Internal: Yes | Interface: WLAN | Depth: 46.2 mm | Antenna: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950