



Iiyama
XUB2293HSU-B7
21.5inch IPS
FHD 100Hz
300cd/m2 1ms
HDMI DP 2xUSB
2.0 Speakers
15cm Height
Adj. Stand (P)

Model: XUB2293HSU-B7

Manufacturer: Iiyama

EAN: 4948570124572

Product Code: 111051

R2,953

The Iiyama ProLite XUB2293HSU-B7 is designed to deliver visual quality with its 21.5-inch diagonal screen and Full HD 1920 x 1080 resolution. Featuring a matte display coating, this monitor reduces glare while providing vibrant images thanks to its 300 cd/m² brightness and a contrast ratio of 1000:1. With technologies like Overdrive and Flicker-Free, it minimizes motion blur and eye strain, making it suitable for long work hours or gaming sessions. It also supports Adaptive-Sync technology to enhance your gaming experience.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Connectivity is made easy with multiple inputs, including HDMI and DisplayPort, along with a built-in USB 2.0 hub for cable management. The monitor's ergonomic design features height, swivel, tilt, and pivot adjustments to find the perfect viewing angle, catering to diverse workspace arrangements. Compliant with multiple environmental standards, this monitor meets performance expectations and contributes positively to your workspace's eco-friendliness.

Product Description: iiyama ProLite XUB2293HSU-B7 - LED monitor - Full HD (1080p) - 21.5" | Device Type: LED-backlit LCD monitor - 21.5" | Energy Class: Class E | Features: USB 2.0 hub | Panel Type: IPS | Aspect Ratio: 16:9 | Native Resolution: Full HD (1080p) 1920 x 1080 at 100 Hz | Pixel Pitch: 0.249 mm | Brightness: 300 cd/m² | Contrast Ratio: 1000:1 / 80000000:1 (dynamic) | Response Time: 1 ms (MPRT) | Colour Support: 16.7 million colours | Colour Gamut: 72% NTSC, 96% sRGB | Input Connectors: HDMI, DisplayPort | Display Position Adjustments: Height, pivot (rotation), swivel, tilt | Screen Coating: Matte | Voltage: AC 100-240 V (50/60 Hz) | Colour: Black, matte | Dimensions (WxDxH) - with stand (lowest position): 49.2 cm x 20.95 cm x 32.85 cm | Weight: 3.9 kg | Environmental Standards: TCO Certified Displays 9 | Compliant Standards: DDC-2B, DDC/CI, RoHS, WEEE, PSE Mark, REACH, ERP, VCCI Class B, EAC, REACH SvHC, UKCA, TUV-GS

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950