




InLine 92502G wire connector Terminal block / D-Sub 25 Green



Model: 92502G

Manufacturer: INLINE

EAN: 4043718346066

Product Code: 1126150

R1,216

Time savings during installation: Quick wiring via screw terminals for 18-26 AWG – tool-assisted with flat-head screwdriver ≤ 2.5 mm.

Dual interface for flexible connection: Equipped with a D-Sub-25 plug and a D-Sub-25 socket – ideal as a compact feed-through or branch point for serial signals.

Versatile industrial use: Suitable for structured wiring in control cabinets, machine control, signal distribution, or test setups.

DIN rail mounting for standard-compliant installation: The integrated DIN rail clip enables direct mounting on mounting rails – quick, workshop-ready, and space-saving.

High signal quality: An insulation resistance of ≥ 10 M Ω at 300 V DC and a rated current of 0.7 A per pin ensure reliable signal transmission – even under continuous load.

The InLine® D-Sub 25 terminal block with combined socket and plug design is designed for structured signal wiring in industrial applications. It combines two serial D-Sub interfaces (male & female) in a compact module. The side-accessible screw terminals with pressure plate allow the

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

connection of wires in the range of 18–26 AWG – tool-assisted with a flat-head screwdriver ≤ 2.5 mm.

The robust plastic housing with pre-mounted DIN rail clip is suitable for quick mounting on top-hat rails. An EVA insulating layer provides protection when mounting on conductive surfaces. Ideal for control technology, prototyping, test stations, or handover solutions.

D-Sub 25 interfaces: 1× female connector, 1× male connector, with mounting threads (UNC #4-40)

Connection technology: Screw terminal with pressure plate

Connection range: 18–26 AWG

Actuation: With flat-blade screwdriver ≤ 2.5 mm

Rated current: 0.7 A per pin

Max. operating voltage: 100 V between two signals

Insulation resistance: $\geq 10 \text{ M}\Omega$ @ 300 V DC

Operating temperature: $-20 \text{ }^{\circ}\text{C}$ to $+105 \text{ }^{\circ}\text{C}$

Insulation layer: EVA insulation on underside

Mounting: Housing for direct mounting on DIN rail

Dimensions: approx. $88 \times 87 \times 51 \text{ mm}$ (W × H × D)