

Akyga AK-B1- 700 power supply unit 700 W 20+4 pin ATX ATX Grey



Model: AK-B1-700

Manufacturer: AKYGA

EAN: 5901720131485

Product Code: 1153347

R1,336

Certification: CE, FCC, RoHS, REACH | On/off switch: Yes | SATA power cable length: 300 mm | SATA power cable length: 150 | Purpose: PC | AC input frequency: 50 Hz | Power protection features: Over current | Cooling type: Active | Power protection features: Over power | Peripheral (Molex) power cable length: 150 | Cabling type: Non-Modular | Depth: 160 mm | Efficiency: 70% | Max output current (-12V): 0.5 A | Power protection features: Overheating | Combined power (+12V): 384 W | Max output current (+12V): 32 A | Peripheral (Molex) power connectors (4-pin): 2 | EPS power connector (4+4 pin): Yes | Power protection features: Short circuit | Power protection features: Over voltage | Fan location: Side | Fan diameter: 12 cm | Package width: 180 mm | Number of SATA power connectors: 5 | AC input voltage: 220 - 230 V | Mean time between failures (MTBF): 100000 h | Max output current (+5V): 38 A | Combined power (+5Vsb): 18.5 W | Package type: Box | Motherboard power cable length: 45 cm | Combined power (+5V): 300 W | Width: 150 mm | Package weight: 1.33 kg | Combined power (-12V): 18.5 W | Product colour: Grey | Package depth: 260 mm | Power supply

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

unit (PSU) form factor: ATX | Power Factor Correction (PFC) type: Passive | Max output current (+3.3V): 35 A | Motherboard power connector: 20+4 pin ATX | Number of fans: 1 fan(s) | Operating temperature (T-T): 5 - 50 °C | ATX version: 2.31 | EPS cable length: 60 cm | PCI Express power cable length: 45 cm | Combined power (+3.3V): 300 W | PCI Express power connectors (6+2 pin): 2 | Package height: 95 mm | Peripheral (Molex) power cable length: 300 | Height: 85 mm | Total power: 700 W | Max output current (+5Vsb): 2.5 A | Weight: 1.26 kg | Compliance certificates: RoHS

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950