



CyberPower CP1200EIPFCRM2U uninterruptible power supply (UPS) Line- Interactive 1.2 kVA 720 W 8 AC outlet(s)



Model: CP1200EIPFCRM2U

Manufacturer: CYBERPOWER

EAN: 4711027798233

Product Code: 1179003

R7,477

Rack capacity: 2U | Operating relative humidity (H-H): 0 - 95% | Weight: 11.6 kg | Form factor: Rackmount | Operating temperature (T-T): 0 - 40 °C | Power source type: AC | Cooling type: Active | Output power: 720 W | AC outlets quantity: 8 AC outlet(s) | USB 2.0 ports quantity: 1 | LED indicators: Yes | Product colour: Black | Ethernet LAN (RJ-45) ports: 2 | RS-232 ports: 1 | Automatic Voltage Regulation (AVR): Yes | Typical backup time at half load: 11.6 min | Input operation voltage (min): 169 V | AC outlet types: C13 coupler | EMI/RFI noise filtering: Yes | Waveform: Pure sine | Input operation voltage (max): 271 V | ECO mode: Yes | Compliance certificates: RoHS | Compliance certificates: CE | USB port type: USB Type-B | Serial interface: Yes | Serial ports quantity: 1 | Output

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

frequency: 50/60 Hz | Display type: LCD | Depth: 274 mm | Power plug: C14 coupler | Heat
dissipation: 17.1 BTU/h | Built-in fan: Yes | Power factor: 0.6 | Battery type: RBP0181 | Output power
capacity: 1.2 kVA | Control type: Buttons | Housing material: Metal | UPS topology: Line-Interactive |
Detachable power cord: Yes | Hot-swap battery: Yes | Number of batteries supported: 1 | Input
frequency: 50/60 Hz | Power protection features: Over voltage | Power protection features: Overload
| Typical backup time at full load: 3.4 min | Battery technology: Sealed Lead Acid (VRLA) | Output
frequency regulation: 1 Hz | Width: 433 mm | Power Factor Correction (PFC) type: Active | USB port:
Yes | Height: 86 mm | Surge protection: Yes | Serial interface type: RS-232

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950