

PowerWalker VI 500 R1U Line- Interactive 0.5 kVA 300 W 4 AC outlet(s)



Model: VI 500 R1U

Manufacturer: POWER WALKER

EAN: 4260074980387

Product Code: 1217986

R4,082

Manual: Yes | Number of batteries supported: 2 | Package height: 150 mm | UPS topology: Line-Interactive | Operating relative humidity (H-H): 0 - 95% | Display type: LCD | Depth: 216 mm | AC outlet types: C13 coupler | Output power factor: 0.6 | Output power capacity: 0.5 kVA | Battery capacity: 7 Ah | Input frequency: 45/55 Hz | USB port: Yes | Typical backup time at half load: 10.3 min | Width: 433 mm | Form factor: Rackmount | Rack capacity: 1U | Emergency Power Off (EPO) connector: Yes | Output frequency regulation: 0.5 Hz | Output voltage regulation: 10% | Battery recharge time: 8 h | Output operation voltage (max): 230 V | Output operation voltage (min): 230 V | Operating temperature (T-T): 0 - 40 °C | Power protection features: Overload | Harmonized System (HS) code: 85078000 | RS-232 ports: 1 | Package width: 537 mm | AC outlets quantity: 4 AC outlet(s) | Waveform: Sine | Battery voltage: 6 V | Weight: 7.6 kg | Product colour: Black | Output power: 300 W | Height: 44 mm | Cables included: USB cable | Typical backup time at full load: 0.8 min | Input operation voltage (max): 290 V | Input operation voltage (min): 165 V

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950