



CyberPower CP1200EIPFCRM2U uninterruptible power supply (UPS) Line- Interactive 1.2 kVA 720 W 8 AC outlet(s)

Model: CP1200EIPFCRM2U

Manufacturer: CYBERPOWER

EAN: 4711027798233

Product Code: 1244205

R7,722

AC outlets quantity: 8 AC outlet(s) | Power source type: AC | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 0 - 95% | Cooling type: Active | Ethernet LAN (RJ-45) ports: 2 | Form factor: Rackmount | Weight: 11.6 kg | Rack capacity: 2U | USB 2.0 ports quantity: 1 | LED indicators: Yes | Output power: 720 W | Product colour: Black | Depth: 274 mm | Output power capacity: 1.2 kVA | Compliance certificates: RoHS | Compliance certificates: CE | Output frequency regulation: 1 Hz | Width: 433 mm | RS-232 ports: 1 | UPS topology: Line-Interactive | Power factor: 0.6 | AC outlet types: C13 coupler | Battery technology: Sealed Lead Acid (VRLA) | Automatic Voltage Regulation (AVR): Yes | Power protection features: Over voltage | Power protection features:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Overload | Typical backup time at full load: 3.4 min | ECO mode: Yes | Housing material: Metal |
Waveform: Pure sine | Serial interface: Yes | Built-in fan: Yes | Height: 86 mm | Number of batteries
supported: 1 | USB port: Yes | Display type: LCD | Hot-swap battery: Yes | Power plug: C14 coupler |
Heat dissipation: 17.1 BTU/h | Battery type: RBP0181 | Serial interface type: RS-232 | Typical backup
time at half load: 11.6 min | Input frequency: 50/60 Hz | Power Factor Correction (PFC) type: Active |
Control type: Buttons | USB port type: USB Type-B | EMI/RFI noise filtering: Yes | Input operation
voltage (min): 169 V | Serial ports quantity: 1 | Output frequency: 50/60 Hz | Detachable power cord:
Yes | Surge protection: Yes | Input operation voltage (max): 271 V

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950