

TP-Link Archer 5G AX1800 Wireless Dual- Band Gigabit Router



Model: ARCHER NX200

Manufacturer: TP-LINK

EAN: 8885020621075

Product Code: 1247694

R6,231

VPN support: PPTP VPN, IPSec VPN , OpenVPN | 4G bands supported: 1500 | WLAN data transfer rate (second band): 1201 Mbit/s | 4G bands supported: 700 | 4G bands supported: 2300 | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Customs product code (TARIC): 8517620000 | Wi-Fi Multimedia (WMM)/(WME): Yes | 4G bands supported: 1800 | 3G standards: DC-HSDPA | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 MHz | WAN connection type: RJ-45 | 4G bands supported: 2100 | 4G bands supported: 800 | Mobile network generation: 5G | Height: 99 mm | Product type: Tabletop router | 4G bands supported: 900 | Access Control List (ACL): Yes | Detachable antenna(s): Yes | Parental control: Yes | Linux operating systems supported: Yes | 4G bands supported: 3700 MHz | 4G bands supported: 3500 | SIM card type: NanoSIM | WPS push button: Yes | On/off switch: Yes | DoS attack prevention: Yes | Output current: 2 A | SIM card slot: Yes | WLAN data transfer rate (first band): 574 Mbit/s | 3G bands supported: 900 | Dynamic DNS (DDNS): Yes | USB port: No | 3G standards: HSPA | 4G standard: LTE-TDD & LTE-FDD | 3G bands supported:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

2100 | 3G standards: HSPA+ | Firewall security: IPv4 SPI Firewall, IPv6 Firewall | Firewall: Yes | Browser supported: Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser | DMZ support: Yes | Depth: 190 mm | Supported network protocols: IPv4, IPv6 | 3G standards: UMTS | 3G bands supported: 850 | DHCP server: Yes | Ethernet LAN: Yes | Port triggering: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Warnings: Do not expose the device to water or moisture. | Warnings: Do not expose the device to extreme temperatures. | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | 5G bands supported: 700 | 5G bands supported: 1800 | 5G bands supported: 2300 | 5G bands supported: 2500 | 5G bands supported: 3700 | 5G bands supported: 850 | 5G bands supported: 3500 MHz | Number of guest networks (5 GHz): 1 | 5G bands supported: 2100 | Number of guest networks (2.4 GHz): 1 | MU-MIMO technology: Yes | 5G bands supported: 2600 | 5G bands supported: 800 | 5G bands supported: 900 | Antenna design: Internal | Windows operating systems supported: Windows 10 | Ethernet LAN data rates: 1000 Mbit/s | Cables included: LAN (RJ-45) | Reset button: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows 7 | Wi-Fi standards: Wi-Fi 4 (802.11n) | Package weight: 1.19 kg | Windows operating systems supported: Windows NT | Antennas quantity: 10 | Windows operating systems supported: Windows XP | Windows operating systems supported: Windows 98SE | Wi-Fi standards: 802.11g | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | Wi-Fi standards: Wi-Fi 5 (802.11ac) | AC input frequency: 50/60 Hz | Package depth: 115 mm | Quick installation guide: Yes | Product colour: White | AC adapter included: Yes | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Power source type: AC | Weight: 610 g | AC input voltage: 100 - 240 V | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Ethernet LAN data rates: 100 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Output voltage: 12 V | Ethernet LAN data rates: 10 | Operating relative humidity (H-H): 10 - 90% | Mac operating systems supported: Yes | Security algorithms: 128-bit WEP | Ethernet WAN: Yes | Package width: 230 mm | WLAN data transfer rate (max): 1800 Mbit/s | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11ax | Security algorithms: WPA | Networking standards: IEEE 802.11b | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Operating temperature (T-T): 0 - 40 °C | DHCP client: Yes | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11a | Ethernet LAN (RJ-45) ports: 3 | Width: 99 mm | Windows operating systems supported: Windows 2000 | Wi-Fi standards: 802.11b | Ethernet LAN interface type: Gigabit Ethernet | Package height: 221 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950