

TP-Link Archer MR202 wireless router Fast Ethernet Dual- band (2.4 GHz 5 GHz) 4G Black



Model: MR202

Manufacturer: TP-LINK

EAN: 8885020625745

Product Code: 1247696

R2,069

Certification: CE, RoHS | Receiver sensitivity: 5 GHz: 11a 54M: -78 dBm 11ac VHT20: -92 dBm 11ac VHT20: -72 dBm 11ac VHT40: -90 dBm 11ac VHT40: -67 dBm 11ac VHT80: -87 dBm 11ac VHT80: -64 dBm 2,4 GHz: 11g 54M: -74 dBm 11n HT20: -91 dBm 11n HT20: -72 dBm 11n HT40: -88 dBm 11n HT40: -69 dBm | VPN support: PPTP VPN, OpenVPN | LED indicators: LAN, Power, WAN, WLAN | DC-in jack: Yes | Stateful Packet Inspection (SPI): Yes | Reset button: Yes | DHCP client: Yes | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11a | Ethernet LAN data rates: 10 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Web-based management: Yes | Networking standards: IEEE 802.11ac | Ethernet LAN data rates: 100 | Product colour: Black | WAN connection type: RJ-45 | DoS attack prevention: Yes | Windows operating systems supported: Windows 98SE | Product type: Tabletop router | Windows operating systems supported: Windows XP | UMTS bands supported: 2100 MHz | Security algorithms: WPA-PSK | Storage

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

relative humidity (H-H): 5 - 90% | Port triggering: Yes | Mac operating systems supported: Yes | DSL WAN: No | Cables included: LAN (RJ-45) | Security algorithms: 128-bit WEP | Firewall security: IP and MAC Address Binding | Operating relative humidity (H-H): 10 - 90% | Port forwarding: Yes | Ethernet LAN interface type: Fast Ethernet | UMTS bands supported: 900 | Guest access: Yes | Windows operating systems supported: Windows 8 | Security algorithms: WPA | Security algorithms: WPA2-PSK | Windows operating systems supported: Windows NT | WLAN data transfer rate (max): 733 Mbit/s | Height: 33.5 mm | DHCP server: Yes | Transmit power: 20dBm(2.4G) 23dBm(5G) | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Browser supported: Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 | Dynamic DNS (DDNS): Yes | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows 7 | DMZ support: Yes | Windows operating systems supported: Windows 2000 | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | 4G standard: LTE-TDD & LTE-FDD | Ethernet LAN (RJ-45) ports: 3 | Width: 174 mm | Mobile network generation: 4G | Firewall: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Operating temperature (T-T): 0 - 40 °C | Number of Ethernet LAN/WAN ports: 1 | 3G standards: UMTS | Output current: 1 A | 3G standards: HSPA | Point-to-point protocol over Ethernet (PPPoE): Yes | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | UMTS bands supported: 850 | WLAN data transfer rate (first band): 300 Mbit/s | 4G: Yes | Output voltage: 12 V | Antenna design: External | 3G/4G USB modem compatibility: No | Wi-Fi standards: Wi-Fi 4 (802.11n) | Universal Plug and Play (UPnP): Yes | Static IP: Yes | Memory card slot(s): No | Ethernet WAN: Yes | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Cabling technology: 10/100Base-T(X) | Plug and Play: Yes | Power source type: DC | Linux operating systems supported: Yes | USB port: No | Quick installation guide: Yes | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 MHz | 4G bands supported: 700 | 4G bands supported: 2300 | 4G bands supported: 2100 | 4G bands supported: 800 | WLAN data transfer rate (second band): 433 Mbit/s | Wi-Fi standards: 802.11a | Wi-Fi standards: 802.11g | 3G: Yes | Antennas quantity: 2 | Wi-Fi standards: 802.11b | Dynamic IP: Yes | Quality of Service (QoS) support: Yes | 4G bands supported: 900 | AC adapter included: Yes | Storage temperature (T-T): -40 - 60 °C | 4G bands supported: 1800 | Depth: 124.5 mm | Supported network protocols: IPv4, IPv6 | Ethernet LAN: Yes | SIM card slot: Yes | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to water or moisture. | Warnings: Do not expose the device to extreme temperatures.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950