

TP-Link Omada Gigabit VPN Router



Model: TL-ER605

Manufacturer: TP-LINK

EAN: 1210002611206

Product Code: 1247729

R1,835

NAT functionality: One-to-One NAT5 Multi-Net NAT Virtual Server Port Triggering5 NAT-DMZ
FTP/H.323/SIP/IPSec/PPTP ALG, UPnP | Certification: CE, FCC, RoHS | DHCP server: Yes | ARP attack
prevention: Yes | VLAN support: Yes | Policy-based routing: Yes | Firewall: Yes | Static route: Yes |
Access Control List (ACL): Yes | ICMP attack prevention: Yes | System event log: Yes | Harmonized
System (HS) code: 85176990 | 3G/4G USB modem compatibility: Yes | URL filtering: Yes | SIM card
slot: No | DMZ support: Yes | Gigabit Ethernet (copper) ports quantity: 4 | DoS attack prevention: Yes
| DSL WAN: No | Universal Plug and Play (UPnP): Yes | VPN tunnels quantity: 20 | SFP WAN: No |
Ethernet interface type: Gigabit Ethernet | Ethernet WAN: Yes | Product colour: Black | Quick
installation guide: Yes | Storage temperature (T-T): -40 - 70 °C | Internal memory: 256 MB | Power
source type: DC | Linux operating systems supported: Yes | Operating relative humidity (H-H): 10 -
90% | Depth: 101 mm | DC-in jack: Yes | Windows operating systems supported: Windows 10 |
Windows operating systems supported: Windows 98SE | Windows operating systems supported:
Windows 8.1 | Windows operating systems supported: Windows Vista | Windows operating systems
supported: Windows XP | Windows operating systems supported: Windows 8 | Cables included: LAN
(RJ-45) | Output voltage: 12 V | Windows operating systems supported: Windows 7 | Reset button:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Yes | Cabling technology: 10/100/1000Base-T(X) | Flash memory: 128 MB | Mac operating systems supported: MacOS | Ethernet LAN data rates: 1000 Mbit/s | AC adapter included: Yes | Ethernet LAN data rates: 100 | Network address translation (NAT): Yes | Operating temperature (T-T): 0 - 40 °C | Height: 25 mm | Ethernet LAN data rates: 10 | Ethernet LAN (RJ-45) ports: 4 | LED indicators: LAN | LED indicators: Power | LED indicators: Status | LED indicators: WAN | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Width: 158 mm | Storage relative humidity (H-H): 5 - 90% | Web-based management: Yes | Security algorithms: FTPES | Input current: 1 A | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Security algorithms: SIPS | Output current: 1 A | Networking standards: IEEE 802.3u

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950