

TP-Link Gigabit Single-Mode WDM Bi- Directional SFP Module



Model: TL-SM321A-2

Manufacturer: TP-LINK

EAN: 1210002612067

Product Code: 1248110

R830

Certification: CE, FCC | Compliance certificates: RoHS | Multi-mode fiber (MMF) supported: No | Package width: 81.5 mm | Product colour: Metallic | Maximum transfer distance: 1000 m | Package depth: 122.5 mm | Operating relative humidity (H-H): 10 - 90% | Input voltage: 3.3 V | Package weight: 60 g | Tx wavelength (max): 1550 nm | Wavelength-division multiplexing (WDM): Yes | Interface type: SFP | Fiber ethernet cabling technology: 1000BASE | Quantity per pack: 1 pc(s) | Single-mode fiber (SMF) supported: Yes | Harmonized System (HS) code: 85369010 | Maximum data transfer rate: 1250 Mbit/s | SFP transceiver standard: BX | Storage temperature (T-T): -40 - 80 °C | Hot-swap: Yes | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3z | Rx wavelength (max): 1310 nm | SFP transceiver type: Fiber optic | Operating temperature (T-T): 0 - 70 °C | Fiber cable diameters supported (core/cladding): 9/125 µm | Fiber optic connector: LC (UPC) | Package height: 38.5 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950