

Supermicro X13SCL-F-B Bulk Intel C262 LGA 1700 micro ATX



Model: MBD-X13SCL-F-B

Manufacturer: SUPERMICRO

EAN: 672042899166

Product Code: 1249593

R9,535

Supported memory module capacities: 16GB | TPM connector: Yes | Supported memory clock speeds: 3600 | Processor socket: LGA 1700 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 3 | Supported memory module capacities: 8GB | Storage temperature (T-T): -30 - 60 °C | Unbuffered memory: Yes | Memory voltage: 1.1 V | ACPI version: 6.4 | RAID support: Yes | Component for: Server | Supported memory clock speeds: 4000 | Supported memory clock speeds: 4400 MHz | Supported storage drive interfaces: SATA III | Ethernet LAN: Yes | Supported memory module capacities: 32GB | Maximum internal memory: 128 GB | VGA (D-Sub) ports quantity: 1 | Number of memory slots: 4 | Wi-Fi: No | Supported memory types: DDR5-SDRAM | Number of M.2 (M) slots: 1 | Memory slots type: DIMM | Ethernet LAN (RJ-45) ports: 2 | RAID levels: 5 | USB 2.0 connectors: 4 | COM ports quantity: 1 | Storage relative humidity (H-H): 8 - 90% | RAID levels: 0 | Operating relative humidity (H-H): 8 - 80% | Ethernet interface type: Gigabit Ethernet | RAID levels: 10 | System Management BIOS (SMBIOS) version: 3.5 | Operating temperature (T-T): -5 - 55 °C | Motherboard chipset: Intel C262 | RAID levels: 1 | BIOS memory size: 32 Mbit | Number of COM connectors: 1 | Processor manufacturer: Intel | USB 2.0 ports quantity: 2 | Compatible processor series: Intel Pentium G | USB 3.2 Gen 1 (3.1 Gen 1)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

connectors: 2 | Motherboard form factor: micro ATX | Motherboard chipset family: Intel | BIOS type: UEFI AMI | Compatible processor series: Intel® Xeon® | Number of SATA III connectors: 8 | Warnings: Adjust adequate ventilation to avoid overheating and potential damage. | PCI Express x4 (Gen 4.x) slots: 2 | Supported memory clock speed (max): 4400 MHz | PCI Express x8 (Gen 5.x) slots: 2 | ECC compatibility: ECC

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950