

Biostar A68N-2100K motherboard mini ITX

Model: A68N-2100K

Manufacturer: BIOSTAR

EAN: 4712960682399

Product Code: 1249625

R1,603

Bundled software: BullGuard Smart Speed LAN | PC health monitoring: CPU | Motherboard form factor: mini ITX | Harmonized System (HS) code: 84733020 | Windows operating systems supported: Windows 7 | Audio output channels: 7.1 channels | Cables included: SATA | Front panel audio connector: Yes | Memory slots type: DIMM | Supported memory types: DDR3-SDRAM, DDR3L-SDRAM | Parallel processing technology support: Not supported | Component for: PC | Windows operating systems supported: Windows 10 | Processor cores: 2 | HDCP: Yes | Supported storage drive interfaces: SATA III | Ethernet interface type: Gigabit Ethernet | Processor model: E1-6010 | S/PDIF out connector: Yes | Windows operating systems supported: Windows 8.1 | Width: 170 mm | LAN controller: Realtek RTL8111H | Memory voltage: 1.25 V | Ethernet LAN: Yes | USB 2.0 ports quantity: 2 | PS/2 ports quantity: 2 | Maximum number of SMP processors: 1 | Supported memory module capacities: 8GB | Supported memory module capacities: 512MB | TPM connector: Yes | Front panel connector: Yes | Supported memory module capacities: 2GB | Supported memory module capacities: 4GB | Depth: 170 mm | USB 2.0 connectors: 2 | PCI Express x16 (Gen 2.x) slots: 1 | Supported memory clock speeds: 1066 | HDMI ports quantity: 1 | Clear CMOS jumper: Yes | Processor

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

manufacturer: AMD | Audio chip: Realtek ALC887 | Motherboard chipset family: AMD | PC health monitoring: Fan | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 2 | Supported memory module capacities: 1GB | PC health monitoring: Temperature | Number of SATA III connectors: 2 | Supported memory clock speeds: 800 | Maximum internal memory: 16 GB | Number of memory slots: 2 | Wi-Fi: No | Number of chassis fan connectors: 1 | Ethernet LAN (RJ-45) ports: 1 | Number of COM connectors: 1 | Drivers included: Yes | Supported memory clock speeds: 1333 | VGA (D-Sub) ports quantity: 1 | CPU fan connector: Yes | ECC compatibility: Non-ECC

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950