

TP-Link 300Mbps Wireless N WiFi Router



Model: TL-WR841N/PL

Manufacturer: TP-LINK

EAN: 6935364091170

Product Code: 1249841

R917

Certification: CE, FCC, RoHS | VPN support: PPTP, L2TP, IPSec | Networking standards: IEEE 802.3 | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Windows operating systems supported: Windows Vista Enterprise | Windows operating systems supported: Windows 7 Professional | VPN Passthrough: Yes | Windows operating systems supported: Windows Vista Home Premium | Windows operating systems supported: Windows XP Home | Windows operating systems supported: Windows 7 Starter x64 | Windows operating systems supported: Windows NT | Windows operating systems supported: Windows Vista Enterprise x64 | Windows operating systems supported: Windows 2000 Professional | Full duplex: Yes | Security algorithms: 128-bit WEP | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: SSID | Windows operating systems supported: Windows Vista Home Premium x64 | Windows operating systems supported: Windows XP Home x64 | Cables included: LAN (RJ-45) | Windows operating systems supported: Windows 7 Home Premium | Windows operating systems supported: Windows 7 Starter | Memory card slot(s): No | Networking standards: IEEE 802.11b | Security algorithms: WPS | Security algorithms: WPA | Windows operating systems supported:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Windows Vista Business | Networking standards: IEEE 802.3u | Ethernet LAN data rates: 10 | Windows operating systems supported: Windows Vista Ultimate | Windows operating systems supported: Windows 7 Ultimate x64 | Windows operating systems supported: Windows XP Professional x64 | Windows operating systems supported: Windows Vista Business x64 | Windows operating systems supported: Windows XP Professional | Weight: 700 g | WLAN data transfer rates supported: 11 | Quick start guide: Yes | WLAN data transfer rates supported: 300 | 3G: No | Package weight: 520 g | Windows operating systems supported: Windows 7 Home Basic | Windows operating systems supported: Windows 7 Ultimate | Windows operating systems supported: Windows 2000 | Power source type: DC | Linux operating systems supported: Yes | Windows operating systems supported: Windows Vista Ultimate x64 | Windows operating systems supported: Windows 7 Enterprise | 3G/4G USB modem compatibility: No | Windows operating systems supported: Windows Vista Home Basic x64 | Windows operating systems supported: Windows 7 Professional x64 | WLAN data transfer rates supported: 54 | Product type: Tabletop router | Windows operating systems supported: Windows 7 Home Basic x64 | Windows operating systems supported: Windows 98SE | Operating relative humidity (H-H): 10 - 90% | Windows operating systems supported: Windows Vista Home Basic | On/off switch: Yes | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows 7 Enterprise x64 | Height: 28 mm | Ethernet LAN data rates: 100 | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WPA-PSK | Rack mounting: No | 4G: No | Output voltage: 9 V | Wi-Fi standards: 802.11g | Wi-Fi standards: Wi-Fi 4 (802.11n) | Stateful Packet Inspection (SPI): Yes | Width: 174 mm | Harmonized System (HS) code: 85176990 | Frequency band: 2.4 GHz | Ethernet LAN interface type: Fast Ethernet | DMZ support: Yes | Dynamic DNS (DDNS): Yes | Detachable antenna(s): No | Port triggering: Yes | Port forwarding: Yes | Product colour: White | AC adapter included: Yes | DoS attack prevention: Yes | DHCP server: Yes | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | DSL WAN: No | Package depth: 202 mm | Product colour: Black | Mac operating systems supported: MacOS | Wi-Fi band: Single-band (2.4 GHz) | Mobile network connection: No | USB port: No | xDSL connection: No | Operating temperature (T-T): 0 - 40 °C | DC-in jack: Yes | Depth: 119 mm | Firewall: Yes | DHCP client: Yes | Ethernet LAN (RJ-45) ports: 4 | Ethernet WAN: Yes | Ethernet LAN: Yes | SIM card slot: No | Security algorithms: 152-bit WEP | Antenna design: External | WLAN data transfer rate (max): 300 Mbit/s | Storage relative humidity (H-H): 5 - 90% | Antennas quantity: 2 | Universal Plug and Play (UPnP): Yes | Reset button: Yes | Cabling technology: 10/100Base-T(X) | Package width: 288 mm | Wi-Fi standards: 802.11b | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package height: 86 mm | Filtering: Yes | Transmit power: 20 dBmW | Firewall security: SPI | Power consumption (typical): 8 W | LED indicators: Power, Status, WLAN | Input current: 0.6 A | Filtering

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

description: IP, MAC, URL | Antenna gain level (max): 5 dBi | Output current: 0.6 A

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950