

**NETGEAR
GS728TP
Managed
L2/L3/L4 Gigabit
Ethernet
(10/100/1000)
Power over
Ethernet (PoE)
Grey**



Model: GS728TP-300EUS

Manufacturer: NETGEAR

EAN: 606449162257

Product Code: 1250054

R8,170

Certification: CE, FCC Class A, RCM, ICES Class A, VCCI, KC, BSMI, UKCA | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Avoid contact of the device with liquid. | Warnings: Follow the safety guidelines for electrical current. | USB Type-A ports quantity: 1 | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Storage temperature (T-T): -20 - 70 °C | Internal memory: 512 MB | Product colour: Grey | Noise level: 26.8 dB | Depth: 257 mm | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.1D | Storage relative humidity

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

(H-H): 0 - 95% | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Power over Ethernet (PoE) power per port: 190 W | Height: 432 mm | Processor manufacturer: ARM | Power consumption (typical): 24 W | Power consumption (max): 226 W | Built-in processor: Yes | Rack mounting: Yes | Width: 440 mm | Operating temperature (T-T): 0 - 50 °C | Power over Ethernet (PoE): Yes | Number of fans: 2 fan(s) | Operating relative humidity (H-H): 0 - 90% | VLAN support: Yes | Flash memory: 64 MB | Processor model: ARM Cortex-A55 | Power source: AC | Weight: 3.78 kg | Processor frequency: 800 MHz | Installed SFP modules quantity: 4 | Switching capacity: 56 Gbit/s | Port mirroring: Yes | MAC address table: 16000 entries | Multicast support: Yes | Packet buffer memory: 1.5 MB | Basic switching RJ-45 Ethernet ports quantity: 24 | Power over Ethernet plus (PoE+) ports quantity: 24 | Latency (10-100 Mbps): 8.864 µs | Access Control List (ACL): Yes | DHCP features: DHCP snooping | Mean time between failures (MTBF): 1751613 h | Heat dissipation: 772.9 BTU/h | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | ARP inspection: Yes | DHCP features: DHCPv6 client | IPv6 routes: 32 | Switch layer: L2/L3/L4 | Number of VLANs: 256 | Access Control List (ACL) IPv4 entries: 100 | Redundant fans support: Yes | Number of multicast groups filtered: 512 | Switch type: Managed | Latency (1 Gbps): 4.691 µs | IPv4 routes: 32

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950