

**NETGEAR
GS728TPP
Managed
L2/L3/L4 Gigabit
Ethernet
(10/100/1000)
Power over
Ethernet (PoE)
Grey**



Model: GS728TPP-300EUS

Manufacturer: NETGEAR

EAN: 606449162356

Product Code: 1250055

R10,385

Certification: CE, FCC Class A, RCM, ICES Class A, VCCI, KC, BSMI, UKCA | Processor manufacturer: ARM | Power consumption (typical): 26 W | Product colour: Grey | Storage relative humidity (H-H): 0 - 95% | Built-in processor: Yes | Operating relative humidity (H-H): 0 - 90% | Operating temperature (T-T): 0 - 50 °C | Power over Ethernet (PoE) power per port: 380 W | VLAN support: Yes | Height: 432 mm | Flash memory: 64 MB | Noise level: 33.3 dB | Width: 440 mm | Rack mounting: Yes | Depth: 257 mm | Storage temperature (T-T): -20 - 70 °C | Power source: AC | Networking standards: IEEE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

802.3ad | Networking standards: IEEE 802.1s | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Power over Ethernet (PoE): Yes | Networking standards: IEEE 802.1D | Weight: 4.11 kg | Power consumption (max): 427 W | Processor model: ARM Cortex-A55 | Processor frequency: 800 MHz | Switching capacity: 56 Gbit/s | Mean time between failures (MTBF): 1252990 h | Networking standards: IEEE 802.1w | Number of fans: 2 fan(s) | Internal memory: 512 MB | IPv6 routes: 32 | Warnings: Follow the safety guidelines for electrical current. | Warnings: Make sure the ventilation of the equipment is not blocked. | IPv4 routes: 32 | Warnings: Avoid contact of the device with liquid. | USB Type-A ports quantity: 1 | Access Control List (ACL): Yes | ARP inspection: Yes | Redundant fans support: Yes | Switch type: Managed | Switch layer: L2/L3/L4 | Latency (10-100 Mbps): 8.871 μ s | Power over Ethernet plus (PoE+) ports quantity: 24 | DHCP features: DHCP snooping | Multicast support: Yes | DHCP features: DHCPv6 client | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Installed SFP modules quantity: 4 | Access Control List (ACL) IPv4 entries: 100 | Number of VLANs: 256 | Basic switching RJ-45 Ethernet ports quantity: 24 | Number of multicast groups filtered: 512 | Latency (1 Gbps): 4.701 μ s | Packet buffer memory: 1.5 MB | MAC address table: 16000 entries

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950